

SPECIFICATION OF

40W AMORPHOUS SILICON SOLAR MODULE

Maximum power (Wp)	40W
Maximum power voltage (V)	47
Maximum power current (A)	0.86
Open circuit voltage (V)	63
Short circuit current (A)	1.03
Size of module (mm)	1250*640*35
P-I-N Junction	double junction
Maximum system voltage (V)	1000V
Temperature coefficients of Isc (%)	+0.09/°C
Temperature coefficients of Voc (%)	-0.33/°C
Temperature coefficients of Pm (%)	-0.22/°C
Temperature Range	-40°C to +85°C
Weight per piece (kg)	14.4
Junction Box	Waterproof, TUV certified
Cell Efficiency (%)	7%
Watt tolerance(%)	±5%
Encapsulant	EVA(Ethylene Vinyl Acetate)
Frame (Material, Corners, etc.)	Anodized Aluminum Alloy
Front glass	3.2mm annealed glass
Back side	Float Glass
Frame (Material, Corners, etc.)	frameless
Standard Test Conditions	AM1.5 100MW/cm ² 25°C
Warranty	90% power for 10years, 80% power for 20 years.



深圳市拓阳新能源科技有限公司

SHENZHEN TUOYANG NEW ENERGY CO., LTD

Tel: +86-755-2305 5561 Mobile: +86-13717084860

www.sztuoyang.com

Email:szsyty@163.com