

QS Solar **Single Glass** 100W Amorphous Thin-Film Module



Product Information Sheet


Advantages

- 40% lighter (only 15.25kg per module and 9.9kg/m²) than regular glass/glass thin film panels
- Perfect for rooftop (esp. rooftop with weight restrictions) and BIPV/BAPV projects
- The reinforced back structure offers the same resistance as regular modules
- Delivers 100 Watts at standard test conditions.

About QS Solar

- QS Solar has his own unique manufacturing process giving the lowest sustainable production cost & reliable product quality
- QS Solar has fully committed to an environmentally friendly production cycle
- QS Solar is ISO 9001 and ISO 14001 Certified

Single Glass 100W Module



Limited Warranties

- 5 Years product warranty
- 90% of the specified minimum output of the module for a 10 years period
- 80% of the specified minimum output of the module for a 25 years period

Installation Cables

Two solar grade UV stable cables compatible with MC4 standard can facilitate a variety of mounting schemes and permit easy field wiring

Benefits

- Generate more power at dawn, during twilight or cloudy days due to higher low light sensitivity. In the same location, thin film panels can generate 10% to 15% more electricity per year than crystalline silicon panels
- Better performance at higher temperature compared to Crystalline Silicon Cells due to lower temperature coefficient. Outdoor panels normally operate at much higher temperature than the standard test temperature 25°C (77 °F). Under most real operating temperature, electricity generated by crystalline modules decrease substantially more than the power generated by Amorphous Silicon modules. This makes Amorphous Silicon Modules the best choice for higher temperature applications
- Less sensitivity to exact mounting angle makes the Amorphous Silicon panels also suitable for none perfect mounting angles on existing buildings and often reduces installation costs because of less complicated mounting structures
- Amorphous Silicon thin film panels require far less silicon materials than traditional crystalline technology, need far less energy during production and do not use any polluting material like other types of thin film panels, thereby saving costs and protecting the environment today and in the future

www.qssolar.com




ELECTRICAL EQUIPMENT,
CHECK WITH YOUR INSTALLER

QS Solar **Single Glass** 100W Amorphous Thin-Film Module


Mechanical Specifications

High reliable glass to glass laminate withstanding standard mechanical loads. Optional aluminum frame for increasing strength and with predrilled mounting holes for easy installation. Aluminum frame has special dripholes to prevent moisture build up.



	Framed
Outside length (mm)	1412±2
Outside width (mm)	1112±2
Thickness (mm) (incl. junction box)	25±1
Thickness (mm) (excl. junction box)	18±1
Weight (kg)	15.25

For detailed installation instructions information, please refer to the **Installation Manual** from QS Solar



- 1 TCO Glass
- 2 EVA
- 3 TPT

Electrical Characteristics

Data at Standard Test Conditions (STC)

STC: irradiance level 1000W/m², spectrum AM 1.5 and cell temperature 25°C

Rated power	Pr	100.0W
Peak power	Pmpp	100.0W
Peak power voltage	Vmpp	94.4V
Peak power current	Impp	1.06A
Open circuit voltage	Voc	115.8V
Short circuit current	Isc	1.27A
Series fuse rating		3A
Minimum peak power	Pmpp min	95.0W

The abbreviation 'mpp' stands for Maximum Power Point

Typical data at Nominal Operating Cell Temperature (NOCT) conditions

NOCT: 800W/m² irradiance level, AM 1.5 spectrum, wind velocity 1m/s, Tamb 20°C

Temperature	TNOCT	45°C
Mpp power	Pmpp	78.9W
Mpp voltage	Vmpp	90.90V
Mpp current	Impp	0.87A
Open circuit voltage	Voc	108.2V
Short circuit current	Isc	1.03A


Temperature coefficients

α Pmpp	-200mW/°C
α Vmpp	-170mV/°C
α Impp	1.3mA/°C
α Voc	-347mV/°C
α Isc	0.9mA/°C

Maximum system voltage: 1000V DC

Typical Characteristics

The graph below shows the typical performance of the solar module at various levels of temperature



References in this QS SOLAR product information sheet are aiming to provide our professional analytic datas to our customers and companies that are involved in the photovoltaic solar energy business. QS group was set up in 1992 and has offices in Asia and Europe and also has a warehouse in France

QS Solar
Powering Your Future

For further information on all QS Solar products contact:

QS Solar
Tel: +86 21 5257 0303 Fax: +86 21 6275 3211
Email: sales@qssolar.com
Website: www.qssolar.com