



GTS Stationary Range

GTS-X battery is designed for Renewable Energy Sources such as Solar and Wind Power.

GTS-X protects our environment using green technology and benefits the worlds Urban and Rural population by generating power economically from a clean source of energy.

Applications

- Soalr and Wind power
- Telecommunication-Outside Plant
- Telecommunication-Central Office
- UPS & BESS
- Electric Utility
- Emergency Power System
- Power Plant



GTS-X Specifications

Model	Nominal Voltage (V)	Nominal Capacity			Dimensions								Weight Approx(Kg)	
		C10	C48	C120	L		W		H		Total Height			
					(mm)	(in)	(mm)	(in)	(mm)	(in)	(mm)	(in)	(Kg)	(lb)
GTS-200X	2	200	222	240	227	8.94	96	3.78	291	11.46	303	11.93	17.50	38.6
GTS-300X	2	300	332	360	227	8.94	133	5.24	291	11.46	303	11.93	24.50	53.9
GTS-400X	2	400	443	480	227	8.94	170	6.69	291	11.46	303	11.93	32.00	70.4
GTS-500X	2	500	552	600	231	9.09	155	6.10	395	15.55	408	16.06	39.50	86.9
GTS-600X	2	600	662	720	231	9.09	180	7.09	396	15.59	408	16.06	47.00	103.4
GTS-800X	2	800	873	960	231	9.09	231	9.09	396	15.59	408	16.06	62.00	136.4
GTS-1000X	2	1000	1094	1200	231	9.09	282	11.10	396	15.59	408	16.06	76.00	167.2
GTS-1200X	2	1200	1315	1440	232	9.13	263	10.35	502	19.76	514	20.24	90.00	198.0
GTS-1500X	2	1500	1641	1800	235	9.25	317	12.48	502	19.76	514	20.24	110.00	242.0
GTS-2000X	2	2000	2188	2400	235	9.25	443	17.44	502	19.76	514	20.24	155.00	341.0

GasTon Battery