

## OPG Series General Information

Model	Nom. Volt.(V)	Nom. Capa. (10hr)(Ah)	Dimention						H Over Terminal		Weight Approx	
			L		W		H		(mm)	(in)	(Kg)	(Ib)
			(mm)	(in)	(mm)	(in)	(mm)	(in)				
OPG2-200	2	200	103	4.06	206	8.12	355	13.99	390	15.37	16.8	37.04
OPG2-250	2	250	124	4.89	206	8.12	355	13.99	390	15.37	20.5	45.20
OPG2-300	2	300	145	5.71	206	8.12	355	13.99	390	15.37	24.5	54.02
OPG2-350	2	350	124	4.89	206	8.12	471	18.56	506	19.94	28.5	62.84
OPG2-420	2	420	145	5.71	206	8.12	471	18.56	506	19.94	33.0	72.77
OPG2-490	2	490	166	6.54	206	8.12	471	18.56	506	19.94	38.5	84.89
OPG2-600	2	600	145	5.71	206	8.12	646	25.45	681	26.83	46.5	102.53
OPG2-770	2	770	253	9.97	210	8.27	471	18.56	506	19.94	56.0	123.48
OPG2-800	2	800	191	7.53	210	8.27	646	25.45	681	26.83	63.5	140.02
OPG2-1000	2	1000	233	9.18	210	8.27	646	25.45	681	26.83	77.0	169.79
OPG2-1200	2	1200	275	10.84	210	8.27	646	25.45	681	26.83	92.0	202.86
OPG2-1500	2	1500	275	10.84	210	8.27	796	31.36	831	32.74	110.0	242.55
OPG2-2000	2	2000	399	15.72	214	8.43	772	30.42	807	31.80	150.0	330.75
OPG2-2500	2	2500	487	19.19	212	8.35	772	30.42	807	31.80	190.0	418.95
OPG2-3000	2	3000	576	22.69	212	8.35	772	30.42	807	31.80	225.0	496.13

## OPS Series General Information

Model	Nom. Volt.(V)	Nom. Capa. (10hr)(Ah)	Dimention						H Over Terminal		Weight Approx	
			L		W		H		(mm)	(in)	(Kg)	(Ib)
			(mm)	(in)	(mm)	(in)	(mm)	(in)				
OPS2-100	2	100	103	4.06	206	8.12	355	13.99	410	16.15	8.1	17.86
OPS2-150	2	150	103	4.06	206	8.12	355	13.99	410	16.15	10.8	23.81
OPS2-200	2	200	103	4.06	206	8.12	355	13.99	410	16.15	12.9	28.44
OPS2-250	2	250	124	4.89	206	8.12	355	13.99	410	16.15	15.4	33.96
OPS2-300	2	300	145	5.71	206	8.12	355	13.99	410	16.15	18.5	40.79
OPS2-350	2	350	124	4.89	206	8.12	471	18.56	526	20.72	21	46.31
OPS2-420	2	420	145	5.71	206	8.12	471	18.56	526	20.72	24.5	54.02
OPS2-490	2	490	166	6.54	206	8.12	471	18.56	526	20.72	28.2	62.18
OPS2-600	2	600	145	5.71	206	8.12	646	25.45	701	27.62	33.4	73.65
OPS2-800	2	800	191	7.53	210	8.27	646	25.45	701	27.62	46.9	103.41
OPS2-1000	2	1000	233	9.18	210	8.27	646	25.45	701	27.62	57.4	126.57
OPS2-1200	2	1200	275	10.84	210	8.27	646	25.45	701	27.62	67.7	149.28
OPS2-1500	2	1500	275	10.84	210	8.27	796	31.36	851	33.53	83.8	184.78
OPS2-2000	2	2000	399	15.72	214	8.43	772	30.42	827	32.58	110	242.55
OPS2-2500	2	2500	487	19.19	212	8.35	772	30.42	827	32.58	139.4	307.38
OPS2-3000	2	3000	576	22.69	212	8.35	772	30.42	827	32.58	164.8	363.38