


4 OPzS200

NON-SPILLABLE RECHARGEABLE SEALED LEAD ACID BATTERY


■ DIMENSION



■ FEATURES

- Transparent containers;
- Special filter installation for acid fog proof;
- Special pole sealed technology;
- Maintenance convenient;
- High quality and high reliability;
- Super long service life.

■ TERMINAL



■ SPECIFICATIONS

Nominal Voltage	2V	Nominal Capacity (C ₁₀)	200Ah (1.80V @ 20°C)	
Dimension	Length 103mm	Approx. Weight	Without electrolyte:12.5kg /with electrolyte:17.2kg	
	Width 206mm	Max Charging Current	40A	
	Height 354mm	Internal Resistance	Full charged@20°C: 0.0008 Ohm	
	Total Height 409mm	Self Discharge	3% of capacity declined per month@20°C	
Capacity Affected by Temp. (10HR)	40°C	20°C	0°C	-15°C
	109%	100%	85%	65%

■ CHARGE

Using Mode	Cycle use	Float use
Charge Voltage (20°C)	2.35~2.40V(-5mV/°C)	2.21~2.25V(-3mV/°C)

4 OPzS200





NON-SPILLABLE RECHARGEABLE SEALED LEAD ACID BATTERY

■ CONSTANT CURRENT DISCHARGE CHARACTERISTICS (20°C)

TIME	1h	3h	5h	10h	24h	48h	72h	100h	120h	240h
CUT-OFF VOLTAGE	1.80	1.80	1.80	1.80	1.80	1.80	1.80	1.80	1.80	1.80
CAPACITY(Ah)	106	150	172	200	230	250	266	280	284	288

■ CONSTANT POWER DISCHARGE CHARACTERISTICS (20°C)

TIME	1h	3h	5h	10h	24h	48h	72h	100h	120h	240h
CUT-OFF VOLTAGE	1.80	1.80	1.80	1.80	1.80	1.80	1.80	1.80	1.80	1.80
CAPACITY(Wh)	192	278	318	370	426	463	492	518	525	533



Issue: SC-4 OPzS200-001-CGB-201604. For the improvement of products and technology, and the appearance of the specifications are subject to change without prior notice. The company has the right of final interpretation.