

■ VRLA (Valve Regulated Lead Acid Battery) UXL(LH) 2000 (2V, 2000AH/10hr)

► Applications

- UPS System
- Communication Equipments
- Renewable Energy(Solar & Wind power)
- Medical Equipments
- Computer Back-up Power
- Security & Alarm Systems
- Power Plants
- Railroad Traffic Signals
- FA Systems

► Technical Features

- Excellent energy-saving capacity combined with high reliability
- Maintenance - Free (No topping up during whole service life)
- Leakproof (Adopted sealed structure)
- Safety Valve for increased reliability against gas generation
- Very low gassing due to the internal gas recombination
- Minimized Self-Discharge
- Excellent recovery following the deep discharge
- 14 years design life at 25 °C ambient temperature
- Self discharge rate: < 2.5% per month at 77°F (25 °C)
- Container & Cover : Acid-resistant ABS resin
Option : UL94-V0 = ABS
- Terminal
Standard : Volt / Nut Type
Option : Nut inserted structure(99.9% pure copper)
- Completely recyclable

※ The AGM battery does not require equalizing charge.

► Specifications

Nominal Capacity (AH)	• 2000
Nominal Voltage (V)	• 2
Dimensions (L*W*H*TH) (mm)	• 472*333*340*372
Weight (kg)	• 149.0
Design life (at 25 °C)	• 14 years
Internal Resistance (mΩ)	• 0.3
Self Discharge (at 25 °C)	• 2.5% / Month
Operating Temperature Range (°C)	• -15 ~ +50
Charge voltage (at 25 °C)	• 2.22V



Standard type

► Discharge Table in Amperes

Final Voltage	1min	5min	15min	30min	45min	1h	3h	5h	8h	10h	12h	24h
1.8V / Cell	4000	3571	2597	1887	1481	1212	541	357	244	200	172	91.7
1.7V / Cell	5405	4444	3030	2041	1600	1307	563	377	253	204	177	91.7
1.6V / Cell	7018	5405	3448	2273	1709	1399	606	400	260	210	177	91.7

