

# ESG series

## ■ VRLA (Valve Regulated Lead Acid Battery) ESG 800 (2V, 800AH/10hr)

### ► Applications

- UPS System
- Communication Equipments
- Renewable Energy(Solar & Wind power)
- Medical Equipments
- Computer Back-up Power
- Security & Alarm Systems
- Power Plants
- Railroad Traffic Signals
- FA Systems

### ► Technical Features

- Excellent energy-saving capacity combined with high reliability
- Maintenance - Free (No topping up during whole service life)
- Leakproof (Adopted sealed structure)
- Safety Valve for increased reliability against gas generation
- Very low gassing due to the internal gas recombination
- Minimized Self-Discharge
- Excellent recovery following the deep discharge
- 10 years design life at 25 °C ambient temperature
- Self discharge rate: < 2.5% per month at 77°F (25 °C)
- Container & Cover : Acid-resistant ABS resin  
Option : UL94-V0 = ABS
- Completely recyclable

※ The AGM battery does not require equalizing charge.

### ► Specifications

Nominal Capacity (AH)	• 800
Nominal Voltage (V)	• 2
Dimensions (L*W*H*TH) (mm)	• 382*171*325*362
Weight (kg)	• 45.0
Design life (at 25 °C)	• 10 years
Internal Resistance (mΩ )	• 0.43
Self Discharge (at 25 °C)	• 2.5% / Month
Operating Temperature Range ( °C)	• -15 ~ +50
Charge voltage (at 25 °C)	• 2.22V



### ► Discharge Table in Amperes

Final Voltage	10min	15min	20min	30min	40min	50min	1h	2h	3h	5h	8h	10h
1.8V / Cell	1027	845	703	584	490	427	395.2	252.7	190.0	116.9	81.4	76.0
1.7V / Cell	1266	1085	938	752	584	506	460	261	190	117	84.0	77.5
1.6V / Cell	1407	1226	1040	768	638	580	506	265	190	124	84.0	77.5

