LUMINOUS

POWER THAT LASTS LONG AND GOES NO DNA NC

Shakti Charge range is the latest innovation in batteries that offers longer service life and longer backup. It is designed with thick tubular plates which are best suited to provide backup in frequent/long power cut areas.



SMART TALL TUBULAR BATTERY







KEY FEATURES

- · Extremely high purity, corrosion-resistant proprietary spine alloy composition ensures longer service life
- · Tubular plate construction ensures uniform distribution of positive active material from extremely long life and
- · Extra strong and flexible oxidation resistant gauntlet for higher performance and extreme long life
- · Plates are specially designed for better charge acceptance.

TECHNICAL SPECIFICATIONS

Model	Nominal Voltage (V)		Dimensions of Container			Electrolyte	Charging Current (Amp)				Weight (Kg.)		Water
			Length (mm)	Width (mm)	Height (mm)		Boost Mode		Trickle Mode		Dry	Filled	Level Indicator
							Starting Current	Finishing Current	Min (mA)	Max (mA)			(No.)
SC 12054	12	110	502	191	377	17.50	11.10	5.5	92	370	22.6	44.3	6
SC 16054	12	135	502	191	377	18.00	13.60	6.8	113	454	27.4	50.0	6
SC 18054	12	150	502	191	377	18.20	15.10	7.6	126	504	28.6	51.2	6



54 MONTHS **WARRANTY***



FACTORY CHARGED BATTERY IN READY TO USE CONDITION



EASY MAINTENANCE WITHLEVEL **INDICATORS**



LONG & TUBULAR PLATES GIVE LONGERLIFE



HIGH DURABILITY WITH SEALED PLASTIC HOUSING

EXCELLENCE A LONG WAY

Luminous Life-Max tall tubular battery delivers unparalleled power back up even at the hardest of times. So when you choose Luminous product, you choose the avant grande technology. That's why, we bring to you an unprecedented 5 YEAR FREE REPLACEMENT WARRANTY battery that allows you to enjoy free replacement, in case of any malfunctioning.



TALL TUBULAR BATTERY





KEY FEATURES

- · Tubular technology with higher acid volume per ampere hour capacity
- HADI spine casting for long service life
- · Minimum maintenance, Rugged battery for tough conditions.
- · Most suitable for deep cycle applications
- · Long service life

TECHNICAL SPECIFICATIONS

Model	Nominal					Electrolyte	Charging Current (Amp)				Weight (Kg.)		Water
	Voitage		Length	Width (mm)	Height (mm)	Volume (Ltrs.)	Boost Mode		Trickle Mode		Dry	Filled	Level Indicator
	(V)		(mm)					Finishing Current		Max (mA)			(No.)
LM 18075	12	150	502	191	440	20.6	18.1	9.1	151.0	605.0	34.4	60.0	6



75 MONTHS WARRANTY*



FACTORY CHARGED BATTERY IN READY TO USE CONDITION



EASY MAINTENANCE WITH LEVEL **INDICATORS**



LONG & TUBULAR PLATES GIVE LONGER LIFE



HIGH DURABILITY WITH SEALED PLASTIC HOUSING

*Conditions apply *Conditions apply