

# Solar Battery



Sealed and Maintenance-free Operation, High Quality and High Reliability, Exceptional Deep Discharge Recovery, Low Self-discharge, Long Service Life, Solid Copper Terminals, Computer-aided Design and Manufacturing, UL, CE, FCC MSDS Approved

## General Series

电池型号 Battery model	额定电压 (V) Rated voltage	额定容量 (AH) Rated capacity	外形尺寸 (mm) External dimensions				参考重量 (KG) Reference Weight	端子形式 Terminal form
			长 Length	宽 Wedth	高 Height	总高 Total Height		
JS-G23	12	100	330	172	215	225	28.0	T9
JS-G24	12	100	407	173	210	236	30.0	T9
JS-G25	12	120	407	173	210	236	34.0	T9
JS-G26	12	150	485	170	242	242	41.5	T9
JS-G27	12	180	522	240	220	245	54.0	T9
JS-G28	12	200	522	240	220	245	57.0	T9
JS-G29	12	250	520	268	220	245	69.0	T9
JS-G30	2	150	172	102	207	227	8.0	T15
JS-G31	2	200	172	111	329	356	13.5	T15
JS-G32	2	300	171	151	330	366	18.8	T15
JS-G33	2	400	210	176	329	366	26.7	T10
JS-G34	2	500	241	172	331	366	31.0	T10
JS-G35	2	600	301	175	331	366	38.0	T10
JS-G36	2	800	410	175	330	365	53.0	T10
JS-G37	2	1000	475	175	330	356	63.0	T10
JS-G38	2	2000	491	351	343	369	132.0	T10
JS-G39	2	3000	710	352	342	369	195.0	T10

## GEL Series

电池型号 Battery model	额定电压 (V) Rated voltage	额定容量 (AH) Rated capacity	外形尺寸 (mm) External dimensions				参考重量 (KG) Reference Weight	端子形式 Terminal form
			长 Length	宽 Wedth	高 Height	总高 Total Height		
CGP100-12S	12	100	330	172	215	225	29.0	T15
CGP100-12	12	100	407	173	210	236	30.5	T15
CGP120-12	12	120	407	173	210	236	34.0	T15
CGP150-12	12	150	485	170	242	242	42.0	T10
CGP200-12	12	200	522	240	220	245	59.0	T10
CGP250-12	12	250	520	268	220	245	69.0	T10
CGP200-2	2	200	172	111	329	356	13.5	T15
CGP300-2	2	300	171	151	330	366	18.8	T15
CGP400-2	2	400	210	176	329	366	26.7	T10
CGP500-2	2	500	241	172	331	366	31.0	T10
CGP600-2	2	600	301	175	331	366	38.0	T10
CGP800-2	2	800	410	175	330	365	53.0	T10
CGP1000-2	2	1000	475	175	330	356	63.0	T10
CGP2000-2	2	2000	491	351	343	369	132.0	T10
CGP3000-2	2	3000	710	352	342	369	195.0	T10