

























PILOT[®] FOR CYCLES PURPOSES

Valve Regulated Lead Acid Batteries





太陽能變電使用系列 For Solar trans power application
 Street light, cloack, motor, portable power, small city power
 街燈、時鐘、抽水馬達、手提式電源、小城市之電源

BATTERY TYPE	NORMINAL VOLTAGE	NORMINAL CAPACITY (20hr)	DIMENSIONS								TERMINAL POSITION	INTERIOR RESISTANCE	WEIGHT		MAX. CHARGING CURRENT (A)	TERMINAL TYPE
			LENGTH		WIDTH		HEIGHT		WITH TERMINAL				Lbs	Kgs		
NUMBER	(V)	(AH)	in	mm	in	mm	in	mm	in	mm		mΩ	Lbs	Kgs	(A)	
PLG7-6	6	7	5.95	151	1.34	34	3.70	94	3.94	100		17.0	2.69	1.22	2.10	D
PLG12-6	6	12	5.95	151	1.97	50	3.70	94	3.94	100		11.0	3.54	1.61	3.60	D.E
PLG4-12	12	4	3.55	90	2.76	70	4.02	102	4.26	108		40.0	3.30	1.50	1.20	D
PLG7-12	12	7	5.95	151	2.56	65	3.70	94	3.94	100		18.5	4.27	1.94	2.10	D.E
PLG12-12	12	12	5.95	151	3.90	99	3.70	94	3.94	100		15.0	8.21	3.73	3.60	D.E
PLG14-12	12	14	5.95	151	3.90	99	3.70	94	3.94	100		15.0	8.21	3.73	4.20	E.J
PLG20-12	12	20	7.13	181	3.00	76	6.58	167	6.58	167		12.0	12.76	5.80	6.00	H
PLG35-12	12	35	7.68	195	5.12	130	6.46	164	7.05	179		8.0	22.44	10.20	10.50	L
PLG45-12	12	45	7.76	197	6.50	165	6.70	170	6.70	170		7.5	31.24	14.2	13.50	L
PLG65-12	12	65	13.78	350	6.54	166	6.85	174	6.85	174		6.0	44.22	20.1	19.50	M
PLG75-12	12	75	13.78	350	6.54	166	6.85	174	6.85	174		5.8	48.18	21.9	22.50	M
PLG85-12	12	85	13.78	350	6.54	166	6.85	174	6.85	174		5.5	52.58	23.9	25.50	M
PLG100-12	12	100	12.92	328	6.58	167	8.43	214	8.74	222		4.2	62.92	28.6	30.00	O
PLG180-12	12	180	19.41	493	8.04	204	8.35	212	9.06	230		3.8	106.5	48.4	54.00	S
PLG200-12	12	200	19.49	495	9.85	250	8.15	207	9.14	232		3.3	128.7	58.5	60.00	Q
PL18-12S	12	18	4.22	107	4.22	107	7.09	180	7.76	197		11.5	12.81	5.82	5.40	P

車輛使用系列
 汽車用、機車用、船舶用、照明用、航空用、搬運車用、大中輕型戰車用

BATTERY TYPE	NORMINAL VOLTAGE	NORMINAL CAPACITY (20hr)	DIMENSIONS								TERMINAL POSITION	INTERIOR RESISTANCE	WEIGHT		MAX. CHARGING CURRENT (A)	TERMINAL TYPE
			LENGTH		WIDTH		HEIGHT		WITH TERMINAL				Lbs	Kgs		
NUMBER	(V)	(AH)	in	mm	in	mm	in	mm	in	mm		mΩ	Lbs	Kgs	(A)	
US6TMF	12	120	11.03	280	10.44	265	8.15	207	9.06	230		3.7	73.26	33.3	36.0	AG
PL100-12HLM (MF31DS)	12	100	13.58	345	6.77	172	8.46	215	9.45	240		4.0	65.78	29.9	30.0	AH
SMF 75D23L	12	60	9.06	230	6.73	171	7.83	199	8.74	222		4.5	40.70	18.5	18.0	AG
MF 135F51	12	120	19.84	504	7.17	182	8.35	212	10.12	257		4.0	69.96	31.8	40.5	AG
MF 160G51	12	160	19.88	505	7.95	220	8.27	210	9.29	236		3.5	97.9	44.5	48.0	AG
MF 210H52	12	210	20.43	519	10.87	276	8.58	218	9.61	244		3.0	131.3	59.7	63.0	AG

混合式太陽能變電使用系列 For Solar trans power application

PL120-12HB	12	120	18.90	480	7.87	200	9.45	240	8.62	219		3.50	86.9	39.5	36.0	AP
PL150-12HB	12	150	18.90	480	7.87	200	9.45	240	8.62	219		3.20	100.3	45.6	45.0	AP
PL180-12HB	12	180	18.90	480	7.87	200	9.45	240	8.62	219		3.00	119.2	54.2	54.0	AP
PL210-12HB	12	210	18.90	480	9.84	250	8.39	213	7.80	198		2.90	136.0	61.8	63.0	AP
PL230-12HB	12	230	18.90	480	9.84	250	8.39	213	7.80	198		2.80	142.8	64.9	69.0	AP
PL250-12HB	12	250	18.90	480	9.84	250	9.61	244	9.06	230		2.70	149.6	68.0	75.0	AP