



Long Life AGM VRLA Battery, Valve Regulated Lead Acid Battery

Applications

Through persistent efforts, the China-based sealed lead acid battery supplier, has brought a wide range of long life Typical applications as below

- Telecommunication systems including exchange board, microwave station, mobile base station, data center, radio and broadcast station;
- Power plant and power transmission system;
- Solar energy and wind turbine system;
- Signal system and emergency lighting system;
- EPS and UPS systems(Known as UPS battery)

Specification

Models	Nominal voltage (V)	Capacity (Ah)	Overall dimensions (mm)				Weight(kg ± 3%)	Terminal	Layout	Bolt
			Length	Width	Height	Overall height				
GFM-200	2	200/10HR	173	111	329	365	13.3	T5	G	M8×16
GFM-300	2	300/10HR	171	151	330	365	18.5	T5	G	M8×16
GFM-350	2	350/10HR	171	151	330	365	20.5	T5	G	M8×16
GFM-400	2	400/10HR	211	176	329	367	26.1	T5	H	M8×16
GFM-425	2	425/10HR	211	176	329	367	26.8	T5	H	M8×16
GFM-500	2	500/10HR	241	171	349	368	31	T5	H	M8×16
GFM-600	2	600/10HR	301	175	331	366	37.7	T5	H	M8×16
GFM-800	2	800/10HR	410	176	330	365	51.6	T5	I	M8×16
GFM-1000	2	1000/10HR	475	175	328	365	62	T5	I	M8×16
GFM-1200	2	1200/10HR	475	175	328	365	68.5	T5	I	M8×16
GFM-1500	2	1500/10HR	401	351	342	378	96.5	T5	J	M8×16
GFM-2000	2	2000/10HR	491	351	343	383	130	T5	K	M8×16
GFM-2500	2	2500/10HR	712	353	341	382	180	T5	K	M8×16
GFM-3000	2	3000/10HR	712	353	341	382	190	T5	K	M8×16

* Product specifications are subject to change without further notice.



Gel Sealed Lead Acid Battery

Applications

- EPS and UPS system;
- Signal system and emergency lighting system;
- Power plant and power transmission system;
- Solar energy and wind turbine system;
- Telecommunication systems such as exchange board, microwave station, mobile base station, data center, radio and broadcast station;

Specification

Models	Nominal voltage (V)	Capacity (Ah)	Overall dimensions (mm)				Weight (kg ± 3%)	Terminal	Layout	Bolt
			Length	Width	Height	Overall height				
FCG12-24	12	24/10HR	165	126	174	174	7.8	T3	B	M6×12
FCG12-26	12	26/10HR	166	175	126	126	8.4	T2	B	M6×16
FCG12-33	12	33/10HR	196	130	155	167	10.1	T3	A	M6×16
FCG12-38	12	38/10HR	197	166	174	174	12.4	T3	B	M6×16
FCG12-42	12	42/10HR	198	166	174	174	13	T3	B	M6×16
FCG12-50	12	50/10HR	229	138	208	212	15.6	T3	A	M6×16
FCG12-55	12	55/10HR	331	174	214	219	18.3	T4	B	M8×16
FCG12-65	12	65/10HR	350	167	178	178	20.3	T3	B	M6×16
FCG12-70	12	70/10HR	260	169	211	215	21.8	T3	A	M6×16
FCG12-75	12	75/10HR	260	169	211	215	22.2	T3	A	M6×16
FCG12-80	12	80/10HR	331	174	214	219	25	T4	B	M8×16
FCG12-90	12	90/10HR	331	174	214	219	28	T4	B	M8×16
FCG12-100	12	100/10HR	331	174	214	219	30.7	T4	B	M8×16
FCG12-120	12	120/10HR	407	174	210	233	34.4	T5	A	M8×16
FCG12-145	12	145/20HR	532	206	212	217	41.6	T4	C	M8×16
FCG12-150	12	150/10HR	484	171	241	241	43.7	T4	A	M8×16
FCG12-160	12	160/10HR	532	206	216	222	48.5	T4	C	M8×16
FCG12-180	12	180/10HR	522	240	219	224	55.6	T5	C	M8×16
FCG12-200	12	200/10HR	522	240	219	224	58.5	T5	C	M8×16
FCG12-220	12	220/10HR	520	269	203	209	68.3	T5	C	M8×16
FCG12-250	12	250/10HR	520	268	220	225	70.3	T5	C	M8×16

* Product specifications are subject to change without further notice.