



Solar

Wind

Mobility

Golf Carts

Medical

Electric Toys



PDC-121000

12V 100.0 AH @ 20-hr.
12V 92.0 AH @ 10-hr.





Rechargeable Sealed Lead Acid Battery
PDC – Deep Cycle AGM Series

TERMINALS (mm)

U: Universal terminals:
Heavy-duty posts with
'nut & bolt' fasteners


POSITIVE

NEGATIVE




Torque: 11.0~14.7 Nxm

DIMENSIONS inch (mm)



L: 12.05 (306)
W: 6.61 (168)
H: 8.27 (210)
HT: 8.50 (216)

Tolerances are +/- 0.04 in.
(+/- 1mm) and +/- 0.08 in.
(+/- 2mm) for height
dimensions. All data subject to
change without notice.



CORPORATE HEADQUARTERS (USA AND INTERNATIONAL EXCLUDING EMEA)

Power-Sonic Corporation
7550 Panasonic Way, San Diego,
California 92154
T: +1 (619) 661 2020
F: +1 (619) 661 3650
E: customer-service@power-sonic.com

POWER-SONIC EUROPE LIMITED (EMEA – EUROPE, MIDDLE EAST AND AFRICA)

3 Buckingham Square,
Hurricane Way, Wickford,
Essex SS11 8YQ
T: +44 (0)1268 560686
F: +44 (0)1268 560902
E: salesEMEA@power-sonic.com

FEATURES

- AGM (absorbent glass mat) technology for superior performance
- Valve regulated, maintenance free spill proof construction
- Specialized paste formulation for true longer life deep cycle performance
- Special additives in the paste ensure excellent performance in deep discharge situations
- Power/volume ratio yielding unrivaled energy density
- Rugged vibration and impact resistant ABS case and cover (UL94-HB) Also available to UL94-V0

APPROVALS

- Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified
- U.L recognized
- ISO9001:2015 – Quality management systems


PERFORMANCE SPECIFICATIONS

| | | |
|--|----------------------------------|----------|
| Nominal Voltage | 12 volts (6 cells) | |
| Nominal Capacity | | |
| 20-hr. (5.0A to 10.50 volts) | | 100.0 AH |
| 10-hr. (9.2A to 10.50 volts) | | 92.0 AH |
| 8-hr. (11.0A to 10.50 volts) | | 88.0 AH |
| 5-hr. (15.8A to 10.20 volts) | | 79.0 AH |
| 1-hr. (58.1A to 9.00 volts) | | 58.1 AH |
| 15-min. (177.7A to 9.00 volts) | | 44.4 AH |
| Approximate Weight | 61.0 lbs. (27.5 kg) | |
| Internal Resistance (approx.) | 5 milliohms | |
| Max Discharge Current (7 Min.) | 289.2 amperes | |
| Max Short-Duration Discharge Current (10 Sec.) | 964 amperes | |
| Shelf Life (% of nominal capacity at 68°F (20°C)) | | |
| 1 Month | | 97% |
| 3 Month | | 91% |
| 6 Month | | 83% |
| Operating Temperature Range | | |
| Charge | 5°F (-15°C) to 122°F (50°C) | |
| Discharge | -4°F (-20°C) to 140°F (60°C) | |
| Case | ABS Plastic | |
| Power Sonic Chargers | PSC-1210000A-C PSC-1210000-PC | |


PDC-121000 12V 100.0 AH @ 20-hr. 12V 92.0 AH @ 10-hr.

Rechargeable Sealed Lead Acid Battery
PDC – Deep Cycle AGM Series

SHELF LIFE & STORAGE



CYCLE LIFE IN RELATION TO DEPTH OF DISCHARGE



CHARGING

Cycle Applications: Apply constant voltage charge at 2.35v/c – 2.45v/c (14.1 – 14.7v for 12v Monobloc) at 20°C. Initial charging current should be set at less than 0.25C Amps. Switch to float charge to avoid overcharging.

“Float” or “Stand-By” Service: Apply constant voltage charge of 2.25v/c – 2.30v/c (13.5 to 13.8 volts for 12v Monobloc) at 20°C. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition.

Temperature Compensation: Charging Voltage for both Cyclic and Standby applications should be regulated in relation to ambient temperature. As temperature rises charging voltage should be reduced to prevent overcharge and increased as temperature falls to avoid undercharge.

For further charging information including temperature compensation factors, see Power Sonic Technical Manual/ Power Sonic Charger specifications.

APPLICATIONS

- Solar
- Wind
- Mobility
- Golf
- Medical
- Electric toys

CORPORATE HEADQUARTERS (USA AND INTERNATIONAL EXCLUDING EMEA)

Power-Sonic Corporation
7550 Panasonic Way, San Diego,
California 92154
T: +1 (619) 661 2020
F: +1 (619) 661 3650
E: customer-service@power-sonic.com

POWER-SONIC EUROPE LIMITED (EMEA – EUROPE, MIDDLE EAST AND AFRICA)

3 Buckingham Square,
Hurricane Way, Wickford,
Essex SS11 8YQ
T: +44 (0)1268 560686
F: +44 (0)1268 560902
E: salesEMEA@power-sonic.com

CHARGERS

Power Sonic offers a wide range of chargers suitable for batteries with a variety of capacities.

Please refer to our website for more information on our switch mode and transformer type chargers.

Please contact our technical department for advice if you have difficulty in locating a suitable charger.

FURTHER INFORMATION

Please refer to our website www.power-sonic.com for a complete range of useful downloads, such as product catalogs, material safety data sheets (MSDS), ISO certification, etc.

