



- FEATURES**
1. Built-in 10A charger (C series)
 2. Battery Reverse connecting protection (AF & C series)
 3. 5V 1A USB charging interface (A & C series)
 4. Inverter and charger can work independent noninterference (SAA-1000C/1000E)
 5. Modified sine wave form output

Technical Parameter

SAA-series

Model	SAA-500A	SAA-1000A	SAA-500C	SAA-1000C	SAA-200AF	SAA-500AF	SAA-1000AF	SAA-1500A
Input voltage	12V							
Output voltage	220V-235V AC							
Rated power	350W	550W	350W	550W	120W	350W	550W	800W
Peak power	500W	1000W	500W	1000W	200W	500W	1000W	1000W
Efficiency	85%							90%
Protections	Overload protection, input over-voltage protection, input low-voltage protection, Overtemperature protection		Overload protection, input over-voltage protection, input low-voltage protection, Overtemperature protection, Battery Reverse protection					
Packed QTY(PCS)	20							
Certifications	ISO,CTA,CE							



- FEATURES**
1. 5V 1A USB interface (SUA-2000C&3000A)
 2. Modified Sine Wave form Output
 3. New connecting terminal screws
 4. Built-in 20A charger (C-series)
 5. Most Competitive price ever



Technical Parameter

SUA-series

Model	Output Voltage	Output Power	Peak Power	Frequency	No-load Current	Working Volt	Voltage Range	Efficiency
SUA-2000A	AC220V(AC110V)	700w	2000w	50Hz	<0.3A	DC12V	10.5-15V	85%-90%
SUA-2000C	220V-230V	700w	2000w	50Hz	<0.3A	DC12V	10.5-15V	85%-90%
SUA-2000AF	AC230V	700w	2000w	50Hz	<0.3A	DC12V	10.5-15V	85%-90%
SUA-3000A	AC220V(AC110V)	900w	3000w	50Hz	<0.3A	DC12V	10.5-15V	85%-90%
SUA-3000BF	AC220V	850w	1700w	50Hz	<0.3A	DC24V	21-30V	>90
SUB-1500AF	AC230V	700w	1500w	50Hz	<0.3A	DC12V	10.5-15V	>90
SUB-1500BF	AC230V	700w	1500w	50Hz	<0.3A	DC24V	21-30V	>90
SUB-2000BF	AC230V	750w	1500w	50Hz	<0.3A	DC24V	21-30V	>90