



Inspiring green-energy since 2003



AE BIFACIAL MONOCRYSTALLINE PV MODULES WITH TRANSPARENT BACKSHEET AE MC-144 Series 430W-445W

144
CELLS

PID
RESISTANT

SALT CORROSION
RESISTANT

SAND
RESISTANT

NH₃
RESISTANT

HIGHLY STABLE
AND TOUGH

TEMPERATURE

Hot spot temperature lower than 85°C
The IEC61215 test shows that with a zero percentage, a small and a 100 percentage of shaded area, respectively hot spots will not exceed 85°C, which is the maximum operating condition.

SAFETY

Instantly reduced temperature, thus eliminating material hazard and ensuring more safety of the module, preventing fire risks caused by hot spots.

GERMAN QUALITY

AE Solar photovoltaic modules are produced using high quality materials, automated robotic lines, German technology and standards.

PERFORMANCE GUARANTEE

AE Solar assures high investment, security and warranty claims by providing linear performance guarantee of 30 years and 12 years of product warranty.

RELIABILITY

Bypass diodes prevent cells mismatching at shaded areas. The lower temperature of hot-spot free modules will eliminate potential cause for back sheet degradation, hence enhancing reliability for longer term.

HIGH RETURNS

This new technology prevents instant falls in the module output, thus increasing the performance ratio up to 30% and return for all types of installations.


PLUS-SORTING

Higher yield due to plus-sorting from 0 up to +5 Wp guarantees the high system efficiency and yield stability.

CERTIFICATES

Lining with international standards, AE Solar Photovoltaic modules are tested and certified under extreme stress conditions and it can bear harsh environment influences.

OUR PERFORMANCE GUARANTEE



30
years
Performance
Guarantee

12
years
Product
Warranty



Deutsche
Qualität
Garantiert

TECHNICAL DATA

AE BIFACIAL SINGLE GLASS Series 430W-445W

SPECIFICATIONS

		AE430MC-144	AE435MC-144	AE440MC-144	AE430MC-144
Nominal Max. Power	P _{max} (Wp)	430	435	440	445
Maximum power voltage	V _{mp} (V)	40.6	40.8	41.0	41.2
Maximum power current	I _{mp} (A)	10.60	10.67	10.74	10.80
Open-circuit voltage	V _{oc} (V)	49.2	49.4	49.6	49.8
Short-circuit current	I _{sc} (A)	11.19	11.26	11.33	11.46
Module efficiency	(%)	19.78	20.01	20.24	20.47
Operating temperature	(°C)	-40 to +85			
Maximum system voltage DC	V (IEC)	1500			
Maximum series fuse rating	(A)	20			
Power tolerance	(%)	0 ~ + 5			
Temp. coefficients of P _{max}	(%/°C)	-0.370			
Temp. coefficients of V _{oc}	(%/°C)	-0.286			
Temp. coefficients of I _{sc}	(%/°C)	0.057			
Nom. Operating cell temp.(NOCT)	(°C)	45±2			

The electrical data apply to standard test conditions (STC): Irradiance of 1000 W/m² with spectrum AM 1.5 and a cell temperature of 25°C.


MATERIAL CHARACTERISTICS

Cell type	Mono-crystalline 166*83 mm
No. of cells	144 Cells (72 Full Cells)
Dimensions	2094 x 1038 x 35 mm
Weight	23 kg
Junction box	IP 68 rated (3 bypass diodes)
Output cable	1 x 4.0mm ² , 350 mm length or customised
Connector type	MC4 / MC4 compatible
Hail resistance	Max. Ø 25 mm, at 23 m/s
Wind load	2400 Pa / 244 kg/m ²
Mechanical load	5400 Pa / 550 kg/m ²


PACKAGING INFORMATION

Packing configuration	64 pcs / double pallet
Loading Capacity	704 pcs / 40HQ
Size / pallet (mm)	2125x1140x2415 mm
Weight	1596kg /double pallet

DIMENSIONS



CERTIFICATES



AE SOLAR

Messerschmittring 54
86343 Königsbrunn
Germany

Tel.: +49 8231 92 92 52 2
Fax: +49 8231 97 82 68 9
Email: sales@ae-solar.com
Web: www.ae-solar.com