








G1 SERIES LIGHT MODULE BM120HL 320~340W



G1 SERIES

LDK redefined the high-efficiency module series by integrating 158.75mm silicon wafers with multi-busbar and half-cut cell technologies. LDK module combined creative technology effectively and extremely improved the module efficiency and power output.

KEY FEATURES

-  Higher system voltages can effectively reduce BOS
-  Lower operating temperature and temperature coefficient, obtain higher profit
-  Significantly reduce the effect of hot spot temperature and shadow shielding
-  Half-cut design for better mechanical load performance
-  Ease of use in more demanding environments

MANAGEMENT SYSTEM

- ISO9001:2015
- ISO14001:2015
- OHSAS18001:2007


PRODUCT CERTIFICATION



LDK is a leading manufacturer and service provider of professional pv cells and modules that can be widely utilized in residence, commerce and ground pv plant.

LDK provides PV products with exceptional power output and reliability by integrating rigorous design, advanced production technology and fully automatic production equipment. Strict quality control and test standards confirm its pursuit of high quality output.

WARRANTY



XinYu LDK Power Supply Technology Co.,Ltd

ADD: No. 1950 SaiWei Avenue, High-Tech, Industrial Development Zone, XinYu City, JiangXi Province, P.R. CHINA

ELECTRICAL PARAMETERS@STC BM120HL-320~340

Max. Power Output Pmax (W)	320	325	330	335	340
Power Tolerance	0~3%	0~+3%	0~+3%	0~+3%	0~+3%
Max. Power Voltage Vmp (V)	34.08	34.36	34.63	34.90	35.17
Max. Power Current Imp (A)	9.39	9.46	9.53	9.60	9.67
Open Circuit Voltage Voc (V)	41.00	41.26	41.53	41.78	42.01
Short Circuit Current Isc (A)	9.91	9.99	10.08	10.16	10.24
Module Efficiency (%)	18.96	19.26	19.56	19.85	20.15

STC (Standard Test Condition): Irradiance 1000W/m², Cell Temperature 25OC, Air Mass 1.5

ELECTRICAL PARAMETERS@NMOT

Max. Power Output Pmax (W)	240	244	248	252	255
Max. Power Voltage Vmp (V)	31.92	32.20	32.40	32.63	32.85
Max. Power Current Imp (A)	7.53	7.58	7.65	7.71	7.77
Open Circuit Voltage Voc (V)	38.50	38.73	39.98	39.22	39.43
Short Circuit Current Isc (A)	8.00	8.06	8.13	8.20	8.26

Nominal Module Operating Temperature (NMOT), Irradiance of 800W/m², Spectrum AM 1.5, Ambient Temperature 20°C, Wind Speed 1m/s

TEMPERATURE COEFFICIENTS

Temperature Coefficients of Pmp	-0.36%/°C
Temperature Coefficients of Voc	-0.29%/°C
Temperature Coefficients of Isc	+0.048%/°C

MECHANICAL PARAMETERS




Cell Type	Mono 158.75×79.38mm
Number of Cells	120pcs (2×(6×10))
Dimensions (L*W*H)	1684×1002×25mm
Weight	14.5kg
Frame	Anodized Aluminum
Junction Box	IP67, 3 bypass diodes
Cable, Length	4mm ² , 350mm

OPERATING CONDITION

Maximum System Voltage(V)	1500 (DC)
Operating Temperature(°C)	-40~+85
Max. Wind Load / Snow Load(pa)	2400/2400
Max. Over Current(A)	20
Application Class	ClassA
Fire Rating	ClassC
NMOT(°C)	42±3

PACKAGE INFORMATION


Per Pallet	42 pcs
40' HQ	1092 (84×13) pcs



*Power measurement tolerance: ±3%

*No notice when product specifications change

Dealer information



XinYu LDK Power Supply Technology Co.,Ltd

ADD: No. 1950 SaiWei Avenue, High-Tech, Industrial Development Zone, XinYu City, JiangXi Province, P.R. CHINA

Email: modulesales@ldksolar.com