

Sun-Pursuit Pro Series

TOPCon Bifacial
108 - cell Module

TW-435HC-1

420-435W

0-3%Positive Tolerance



Monocrystalline




Half Cell



10BB



Grade A



• MODULE FEATURES



High Efficiency

TOPCon technology improves efficiency, increases power generation, and contributes to lower LCOE.



Lower Heat Spot Risk

Innovative circuit design and “Half Cell” structure decrease the temperature of heat spots and effectively reduce power loss.



Excellent Low-light Performance

Reliable performance in low-light conditions such as in the morning, at dusk or during raining days.



Resilient to Extreme Weather

Carefully selected materials ensure the module still works well under the condition of 2400Pa wind load and 5400Pa snow load.



PID Resistant

High quality solar cell and advanced processing technology contribute to excellent PID resistance performance.



Double-sided electricity generation

Power can be generated on both sides to support additional output gains of up to 25%. The multi-busbar half-cut technology can boost energy density to deliver higher output.


• Quality Certification



• Product Qualification



• Performance Warranty



15 Years Product Warranty

30 Years Linear Power Warranty

TW-435HC-1

•Product Specification•

Cell Type	Mono crystalline
Cell Quantity	108 cell
Cell Size(mm)	182*91
Module Size (mm)	1722*1134*30
Module Weight (kg)	21.3
Glass Thickness(mm)	2.0
Frame Material	Anodized aluminum alloy
Junction Box	IP68
Cable/Connector	4mm ² , MC4compatible
Cable Length	+300mm/-300mm; or Customize
Max System Volt(V)	1500V DC
Max Fuse Rate(A)	25
Power Tolerance(%)	0~+3%

•Electrical Characteristics•

STC standard performance >>>

Power Level	420	425	430	435
Pmax(W)	420	425	430	435
Vmp(V)	32.21	32.41	32.61	32.81
Imp(A)	13.06	13.13	13.20	13.28
Voc(V)	37.91	38.11	38.31	38.51
Isc(A)	14.03	14.10	14.17	14.24
Module Efficiency(%)	21.51	21.76	22.02	22.28

NOCT standard performance >>>

Power Level	420	425	430	435
Pmax(W)	316	319	323	327
Vmp(V)	29.73	29.93	30.13	30.33
Imp(A)	10.65	10.68	10.74	10.80
Voc(V)	35.38	35.58	35.88	36.18
Isc(A)	11.29	11.35	11.41	11.47


•Bifacial output-backside power gain•

5%Pmax(W)	441	446	452	457
5% Module Efficiency	22.58	22.85	23.12	23.39
15% Pmax(W)	483	489	495	500
15% Module Efficiency	24.73	25.03	25.32	25.62
25% Pmax(W)	525	531	538	544
25% Module Efficiency	26.89	27.21	27.53	27.85



•Temperature Characteristics•

Operating Temp(°C)	-40~85
Operating Humidity(°C)	5~85
Hail Load Tolerance	25mm hailstone with velocity of 23m/s
Temp Coefficient	-0.340
Temp Coefficient Isc (%/°C)	0.04
Temp Coefficient Voc (%/°C)	-0.25
Operating Temp (°C)	44±2

•Engineering Drawings•



•I-V Curve•



•Packaging Info•

Pieces per Pallet	36
Size of Packaging(mm)	1750*1125*1270
Weight of per Pallet(kg)	792
Pieces per Container	936
Size of Container	40'HC



Add: Shangman Industrial Park, Caobu Town
Rudong County, Nantong City, Jiangsu Province, China
Tel: 86-513-81900128
Web: www.techwisesolar.com
Email: salesdept@techwisesolar.com

All data and specifications included in this brochure
may subject to be modified without notice.
All Rights reserved by TechWise Solar Co.
(Feb 2023 V2 Edition)