LEAD ACID BATTERIES 300Ah-12V

SPECIFICATIONS



SPECIFICATIONS		
Battery Type	:	TT300
Rated Capacity at 20 hour Rate	:	300Ah
Battery Nominal Voltage	:	12V
Dimensions		
Length	:	503±3mm
Width	:	189±2mm
Height up to Terminal	:	354±3mm
Fully Charged Battery		
Electrolyte Specific Gravity at 27°C	:	1.250 ± 0.010
Battery Weight (with electrolyte)	:	76Kg.

ELECTRICAL PERFORMANCE

20 Hour Rate to 10.80V	300.0Ah
10 Hour Rate to 10.80V	264.0Ah
5 Hour Rate to 10.80V	219.9Ah
3 Hour Rate to 10.80V	157.6Ah
1 Hour Rate to 10.50V	94.6Ah
Loss of capacity on storage per month at 27°C	
Percentage (%) of Ampere-hour-Efficiency	
Percentage (%) of Watt-hour-Efficiency	
	10 Hour Rate to 10.80V 5 Hour Rate to 10.80V 3 Hour Rate to 10.80V 1 Hour Rate to 10.50V th at 27°C ciency

BATTERY CHARGING

Constant Voltage Charging (CV)	Maximum Charging current	42.0A
	Cyclic use	14.40±0.05V
	Float use	13.80±0.05V
Constant Current Charge (CC)	Maximum Charging current	21.0A

BATTERY DIMENSIONS

