

All-in-one Solar Charge Inverter


HF4850U80-H (Max.Voc: 500V; Rated input voltage: 110/120V)



Performance characteristics

- Load friendly: Stable sine wave AC output via SPWM modulation
- Supports a wide range of battery technology: GEL, AGM, Flooded, LFP, and program.
- Dual LFP battery activation method: PV&mains
- Uninterrupted power supply: simultaneous connection to utility grid/generator and PV
- Intelligent programming: the priority of the output from different energy sources can be set
- High energy efficiency: up to 99.9% MPPT capture efficiency
- Instant viewing of operation: the LCD panel displays data and settings ,while you can also be viewed using the app and webpage
- Power saving: power saving mode automatically reduces power consumption at zero-load
- Efficient heat dissipation: via intelligent adjustable speed fans
- Multiple safety protection functions: short circuit protection, overload protection, reverse polarity protection, and so on.
- Working without battery under special conditions.

Product characteristics



①	Overload Protector	⑨	Dry Contact Port
②	ON/OFF Rocker Switch	⑩	Cooling Fan
③	AC Input Port	⑪	Battery Port
④	AC Output Port	⑫	Cooling Fan
⑤	Grounding Screw Hole	⑬	PV Port
⑥	RS485-2 Communication Port (For BMS)	⑭	Light Touch Button
⑦	USB Communication Port	⑮	Indicator Light
⑧	RS485-1 Communication Port	⑯	LCD Screen



Parameters

Model	HF4850U80-H	Adjustable
Battery Input		
Battery type	Sealed, Flood, GEL, LFP, Ternary	√
Rated Battery Input Voltage	48V (Minimum Startup Voltage 44V)	
Hybrid Charging Maximum Charging Current	80A	√
Battery Voltage Range	40Vdc~60Vdc ± 0.6Vdc(Undervoltage Warning/Shutdown Voltage/Overvoltage Warning/Overvoltage Recovery...)	√
Solar Input		
Maximum PV Open-circuit Voltage	500vdc	
PV Working Voltage Range	120-500Vdc	
MPPT Voltage Range	120-450Vdc	
Maximum PV Input Current	18A	
Maximum PV Input Power	5200W	
Maximum PV Charging Current	80A	√
AC Input (generator/grid)		
Mains Maximum Charging Current	40A	√
Rated Input Voltage	110/120Vac	
Input Voltage Range	(90Vac~140Vac)±2%	
Frequency	50Hz/ 60Hz (Automatic Detection)	
Mains Charging Efficiency	>95%	
Switch Time (bypass and inverter)	10ms(Typical Value)	
Maximum Bypass Overload Current	63A	
AC Output		
Output Voltage Waveform	Pure Sine Wave	
Rated Output Voltage (Vac)	120Vac (100/105/110Vac)	√
Rated Output Power (VA)	5000 (4100/4300/4500)	
Rated Output Power(W)	5000 (4100/4300/4500)	
Peak Power	10000VA	
On-load Motor Capacity	4HP	
Output Frequency Range(Hz)	50Hz±0.3Hz/60Hz±0.3Hz	√
Maximum Efficiency	> 90%	
No-load Loss	Non Energy-saving Mode: ≤50W Energy-saving Mode: ≤5W (Manual Setup)	
General		
Certificate	CE(IEC62109-1)/CETL(UL 1741 CSA C22.2 NO.107.1)	
EMC Certification Level	EN61000	
Working Temperature Range	-15°C ~ 55°C	
Storage Temperature Range	-25°C ~ 60°C	
Humidity Range	5% to 95%(Conformal Coating Protection)	
Dimensions	426mm*322mm*126mm	
Weight (KG)	11.6	

