



# 108HC M10 TPC SL All Black Module

108 Half-Cut Monocrystalline 420W – 440W

## 22.5%

Utilizes the latest M10 size super high efficiency TOPCon N-type cells. Half cut design further reduces cell to module (CTM) losses.

## Stability & Looks

Enhanced frame design to withstand higher wind, snow, and other mechanical stresses. Framed Glass-Backsheet aesthetic is ideal for high visibility installation.

## High Energy Yield



Highest Efficiency & Low temperature coefficient of N-type TOPCon Solar Cells enable High Energy yield

## High Reliability

TOPCon cells, based on N-type silicon result in low LID, reducing annual degradation and guaranteeing more power throughout the lifetime.

## No Compromise Guarantee

25 Year Product Warranty  
25 Year Linear Performance Guarantee



Highly efficient N-type Solar Cells based on TOPCon technology

Low LCOE enabled by High Power Output & Low BOS Cost

1% First year degradation & 0.4% Annual Power degradation

### World-class Quality

- Heliene's fully automated manufacturing facilities with state-of-the-art robotics and computer aided inspection systems ensure the highest level of product quality and consistency
- All manufacturing locations are compliant with international quality standards and are ISO 9001 certified
- Heliene modules have received Top Performer rankings in several categories from PV Evolution Labs (PV EL) independent quality evaluations

### Bankable Reputation

- Established in 2010, Heliene is recognized as highly bankable Tier 1 manufacturer of solar modules and has been approved for use by the U.S. Department of Defense, U.S. Army Corps of Engineers and from numerous top tier utility scale project debt providers
- By investing heavily in research and development, Heliene has been able to stay on the cutting edge of advances in module technology and manufacturing efficiency


### Local Sales, Service, and Support

- With sales offices across the U.S. and Canada, Heliene prides itself on unsurpassed customer support for our clients. Heliene has become the brand of choice for many of the leading residential installers, developers and Independent Power Producers due to our innovative technology, product customization capability and just in time last-mile logistics support
- Local sales and customer support means answered phone calls and immediate answers to your technical and logistics questions. We understand your project schedules often change with little warning and endeavor to work with you to solve your project management challenges





Dimensions for 108HC M10 TPC SL All Black Series Modules



Electrical Data (STC)

Peak Rated Power*	$P_{mpp}$ (W)	440	435	430	425	420
Maximum Power Voltage	$V_{mpp}$ (V)	32.98	32.76	32.49	32.23	31.96
Maximum Power Current	$I_{mpp}$ (A)	13.36	13.32	13.28	13.23	13.18
Open Circuit Voltage*	$V_{oc}$ (V)	38.63	38.50	38.42	38.29	38.16
Short Circuit Current**	$I_{sc}$ (A)	14.30	14.22	14.13	14.05	13.98
Module Efficiency	Eff (%)	22.49	22.24	21.98	21.73	21.47
Maximum Series Fuse Rating	MF (A)	30	30	30	30	30
Power Sorting Range		[- 0/+3%]				

STC - Standard Test Conditions: Irradiation 1000 W/m<sup>2</sup> - Air mass AM 1.5 - Cell temperature 25 °C,  
 \* $P_{mpp}$  Production Tolerance ± 3%,  $V_{oc}$  Production Tolerance ± 3%, \*\* $I_{sc}$  Production Tolerance ± 4%

Electrical Data (NMOT)

Maximum Power	$P_{mpp}$ (W)	334	330	326	323	319
Maximum Power Voltage	$V_{mpp}$ (V)	31.58	31.37	31.11	30.86	30.60
Maximum Power Current	$I_{mpp}$ (A)	10.58	10.53	10.49	10.46	10.42
Open Circuit Voltage	$V_{oc}$ (V)	36.99	36.86	36.79	36.66	36.53
Short Circuit Current	$I_{sc}$ (A)	11.53	11.46	11.39	11.33	11.27

NMOT - Nominal Module Operating Temperature:  
 Irradiance at 800W/m<sup>2</sup>, Ambient Temperature 20°C, Wind speed 1m/s

Mechanical Data

Solar Cells	108 Half-Cut, M10, 182mm, TOPCon N-type Cells
Module Construction	Framed Glass-Backsheet
Dimensions (L x W x D)	1725 x 1134 x 35 mm (67.91 x 44.65 x 1.38 inch)
Weight	21.5 kg (47.4 lbs)
Frame	Double Webbed 15-Micron Anodized Aluminum Alloy
Glass	3.2mm Low-Iron Content, High-Transmission, PV Solar Glass with Anti Reflective Coating
Junction Box	IP-68 rated with 3 bypass diodes
Output Cables	4mm <sup>2</sup> (12AWG), 1.2-meter Symmetrical Cables (Standard) 0.3-meter Symmetrical Cables (Optional)
Connectors	Multi-Contact/ Stäubli MC4

Certifications

UL Certification UL61215, UL61730 pending

Temperature Ratings

Nominal Module Operating Temperature (NMOT)	+42°C(±2°C)
Temperature Coefficient of $P_{max}$	-0.30%/°C
Temperature Coefficient of $V_{oc}$	-0.25%/°C
Temperature Coefficient of $I_{sc}$	0.045%/°C

Maximum Ratings

Operational Temperature	-40°C to +85°C
Max System Voltage	1500V
Mech. Load Test (Front)	113psf/ 5400Pa
Mech. Load Test (Back)	50 psf / 2400 Pa
Fire Rating	Type 1



Warranty

25 Year Product Warranty	
25 Year Linear Power Guarantee	

Packaging Configuration

Modules per Pallet 40' Container:	31 pieces
Modules per 40' Container:	806 pieces
Modules per Pallet 53' Trailer:	28 pieces
Modules per 53' Trailer:	672 pieces

I-V Curves for 108HC M10 TPC SL All Black Series Modules



The specifications and key features contained in this datasheet may deviate slightly from our actual products due to the ongoing innovation and product enhancements. Helene Inc. reserves the right to make necessary adjustment to the information described herein at any time without prior notice. PV modules should be handled and installed only by qualified people. Please carefully read safety and installation instructions available for download from Helene website before using Helene PV modules. For warranty details, please refer to Product Warranty Document, also available for download from Helene website.