

ESS PRO Lithium Battery Storage System

6KW/5KWH, 6KWH/10KWH, 6KW/15KWH, 6KW/20KWH



Main Features

- All in one system, built inside with 48V lithium battery module, 6kw hybrid solar inverter, Solar/AC Charger.
- Modular & Stacked Design for easy installation and expansion.
- Smart BMS built inside, with communication protocol.
- 5 Years Warranty.
- LiFPO4 cells cycle time Up to 6000 times charge/discharge cycles life
- With 120A mppt Solar charging and AC Charging function
- With all around protection
- DOD 80%, warranty 5 years, 10+ years life design

STORAGE SOLAR SYSTEM

CE UN38.3 MSDS IEC62619 IEC62619
www.sakopower.com

SAKO
SINCE 1993

SPECIFICATION	ESS PRO 6KW/5KWH	ESS PRO 6KW/10KWH	ESS PRO 6KW/15KWH	ESS PRO 6KW/20KWH
INVERTER / CHARGER				
Inverter Type	6KW/48V Hy brid	6KW/48V Hy brid	6KW/48V Hy brid	6KW/48V Hybrid
Rated Output Power	6KW	6KW	6KW	6KW
Output Voltage Waveform	Pure Sine Wave	Pure Sine Wave	Pure Sine Wave	Pure Sine Wave
Output Voltage	230VAC 50HZ	230VAC 50HZ	230VAC 50HZ	230VAC 50HZ
Low DC Warning Voltage	45.8Vdc	45.8Vdc	45.8Vdc	45.8Vdc
Low DC Cut-off Voltage	44.8Vdc	44.8Vdc	44.8Vdc	44.8Vdc
Low DC Warning Return Voltage	46.8Vdc	46.8Vdc	46.8Vdc	46.8Vdc
Total Charging Current(Grid+solar)	120A Max.	120A Max.	120A Max.	120A Max.
Bulk Charging Voltage	57.6Vdc	57.6Vdc	57.6Vdc	57.6Vdc
Float Charging Voltage	56.0Vdc	56.0Vdc	56.0Vdc	56.0Vdc
LITHIUM IRON BATTERY				
Normal Battery Modular	51.2V100Ah*1	51.2V100Ah*2	51.2V100Ah*3	51.2V100Ah*4
Normal Capacity(25°C , 0.2C)	5.12KWh	10.24KWh	15.36KWh	20.48KWh
Nominal Battery Voltage	51.2Vdc	51.2Vdc	51.2Vdc	51.2Vdc
Nominal Capacity	100AH	200AH	300AH	400AH
Max.Charge Current	150A 1Sec.	300A 1Sec.	450A 1Sec.	600A 1Sec.
Max.Discharge Current	50A	100A	150A	200A
Operation Voltage Range	44.8Vdc ~ 58.4Vdc	44.8Vdc ~ 58.4Vdc	44.8Vdc ~ 58.4Vdc	44.8Vdc ~ 58.4Vdc
Operation Temperature	-10°C ~ +50°C	-10°C ~ +50°C	-10°C ~ +50°C	-10°C ~ +50°C
AC INPUT				
Nominal Input Voltage		230Vac		
Low Loss Voltage		170Vac ± 7(UPS), 90Vac ± 7(Appliances)		
Low Loss Return Voltage		180Vac ± 7(UPS), 100Vac ± 7(Appliances)		
High Loss Voltage		280Vac ± 7		
High Loss Return Voltage		270Vac ± 7		
Max. AC Input Voltage		300Vac		
Nominal Input Frequency		50Hz / 60Hz(Auto detection)		
AC Charging Current		120A Max.		
SOLAR INPUT				
Nominal PV Voltage		360Vdc		
PV Array MPPT Voltage Range		120Vdc~450Vdc		
Max. PV Array Open Circuit Voltage		500Vdc		
Solar Charging Current		120A Max.		
PROTECTION				
Protection	Overcharge protection、Overdischarge protection、Overcurrent protection、Shortcircuit protection、Overtemperature protection			
AMBIENT				
Noise(dB)	< 30°C < 40dB (1 meter)			
Working Temperature	-10°C ~ +50°C			
Humidity	0~95% (no condensation)			
Sea Level(m)	≤1500			
OTHERS				
Efficiency	92.0%			
Warranty	5 Years			

STORAGE SOLAR SYSTEM