

Batteries

# Turbo H3 Series

7.1kWh / 9.5kWh  
High Voltage Battery



## FEATURES



Powered by **CATL** LiFePO<sub>4</sub> battery cells



The Lowest charging temperature (-20°C) in the market



Support up to 6 units parallel connections



IP65 outdoor design



Module auto recognition



Remote firmware upgrade and online diagnosis

# Turbo H3 Series

Model	TB-H3-7.1			TB-H3-9.5		
<b>Electrical Parameters</b>						
Nominal Voltage [V]	307.2			409.6		
Nominal Capacity [Ah]	23			23		
Nominal Energy [kWh] <sup>[1]</sup>	7.1			9.5		
Usable Energy (90%DOD) [kWh]	6.4			8.5		
Voltage Range [V]	259.2 ~ 345.6			345.6 ~ 460.8		
Max. Continuous Charging / Discharging Current [A]				18.4		
Peak Current [A]				23		
Peak Power	7.5kW			10kW		
<b>General</b>						
Battery Type	LiFePO <sub>4</sub>					
Size (Width * Height * Depth) [mm]	530 * 886 * 245			530 * 1000 * 245		
Net Weight [kg]	95			125		
Scalable	1	2	3	1	2	3
	7.1kWh	14.2kWh	21.3kWh	9.5kWh	19kWh	28.5kWh
	4	5	6	4	5	6
	28.4kWh	35.5kWh	42.6kWh	38kWh	47.5kWh	57kWh
Enclosure	IP65 ( Indoor or Outdoor)					
Installation Type	Wall - mounted / Floor - mounted					
Cooling Type	Natural					
Communication Port	CAN, RS485					
Ambient Temperature Range [°C] <sup>[2]</sup>	-20 ~ +55					
Operation Humidity	5 ~ 95%					
Altitude [m]	≤ 2000					
Warranty <sup>[3]</sup> [years]	10					
Cycle Life	6000 @ 85% DOD / 25°C / 0.33C / 60% EOL					
<b>Certification</b>						
Certificates	IEC 62619, IEC 62040-1, IEC 62477-1, IEC 61000-6-1 / 3, UN 38.3					

[1] Nominal Energy: 100% DOD, 0.33C charge & discharge at +25°C (test conditions).

[2] Ambient temperature: charging (-17 ~ +53°C). discharge (-17 ~ +53°C).

[3] Condition apply: refer to Renac Power Battery Warranty Policy.