

SkyHawk M-type Module Specification

Monocrystalline 6X18 Solar Modules for Salt Field Type

182mm / M10 Solar Cell

405Wp / 410Wp



The highest Mechanical Load Test in PV Industry



Better LCOE



Improved module power output performance by reducing module working temperature



Advanced Non-Destructive Cutting Technology



World's best PID resistant



Multi Busbar Technology



The toughest Salt Mist Test in PV Industry

Green Energy

Made in Taiwan



Sustainable Development



SkyHawk M-type Module Specification(182mm / M10 Solar Cell) Monocrystalline 6X18 Solar Modules for Salt Field Type 390-410Wp



Electrial Data

Model Name	TS54-BMH-390 H1	TS54-BMH-395 H1	TS54-BMH-400 H1	TS54-BMH-405 H1	TS54-BMH-410 H1		
Max. power at STC	Pmax	W	390	395	400	405	410
Max. power voltage	Vmp	V	30.22	30.32	30.42	30.52	30.62
Max. power current	Imp	A	12.91	13.03	13.15	13.27	13.39
Open circuit voltage	Voc	V	36.82	36.90	36.98	37.06	37.14
Short circuit current	Isc	A	13.64	13.71	13.78	13.85	13.92
Module Conversion Eff.	%		20.0%	20.2%	20.5%	20.8%	21.0%

* Under Standard Test Condition(1,000W/m²,25°C,AM 1.5): Power Tolerance ±3%
* Module Conversion Eff. (%) = [(Max power at STC(w) / ((Solar Module Area(m²) x 1000 (w/m²)))] x 100%

General Data

Cell type	M10 Monocrystalline
Cell per module	Mono-crystalline silicon solar cell (108 pcs)
Front	Low-iron tempered glass
Encapsulant Film	Low water vapor transmission rate (WVTR) material
Rear	Anti-Salt Mist composite film
Frame	Anti-Salt Mist aluminum (silver/black)
Junction Box	IP68
Connector	EVO-2 Compatible
Cable	1500mm / 4mm ²



Temperature Coefficient

Nominal Operating	NOCT	°C	45±2
Cell Temperature			
TC Isc	α	%/°C	+0.06
TC Voc	β	%/°C	-0.27
TC Pmax	γ	%/°C	-0.35

Operation Conditions


Max. system voltage	1500V
Module fire resistance class	Class C
Protection Class (IEC 61140)	Class II
Series fuse rating	25 A
Number of bypass diodes	3
Temperature range	-40 to +85°C
Max. mechanical load	7100 pa(front side) 5400 Pa(rear side)

* Please follow installation manual provided by TSEC

Module Dimensions and Weight

Dimension	1722 x 1133 x 40 mm
Weight	23 Kg

IV Curve





Certifications

- IEC 61215:2016、IEC 61730-1:2016 & IEC 61730-2:2016
- ISO 9001:2015 Quality management system
- ISO 14001:2015 Environmental management system
- ISO 45001:2018 Occupational health and safety management system



Engineering Drawing(mm)



Warranty

- 12-year materials and workmanship warranty
- 25-year linear power warranty

Made in Taiwan * The information in this document is subject to change without notice * TSEC reserves the rights of final interpretation and revision of datasheet. Version: Fourth edition, April 2023.

TSEC Corporation

Taipei Headquarters | 8F., No.225, Sec3, Beixin Rd., Xindian Dist., New Taipei City 231, Taiwan, R.O.C

T +886-2-2912-2199 F +886-2-2917-5399 M taiwan.sales@tsecpv.com(Sales Contact) epc@tsecpv.com(EPC Construction Service)