Cell Battery specifications			
Item	General Parameter		Remark
Rated Capacity	Typical	50Ah	Standard discharge (0.2C5A)
	Minimum	50Ah	after Standard charge
Nominal Voltage	3.2V		Mean Operation Voltage
	≪0.65 mΩ		Internal resistance measured at AC 1KHZ
Internal Impedance			after 50% charge
			The measure must uses the new batteries
			that within one week after shipment and
	 Thickness/厚度:Max 24.5mm		cycles less than 5 times
Dimension	Width/宽度: Max 140.5mm		Initial Dimension
	Height/高度: Max 160.5mm		
Weight	1.15kg		APPROX
	Constant Current 0.33C5A		Charge time : Approx3.5h
Standard charge	Constant Voltage 3.65V		
	0.02C5A cut-off Constant Current 1C5A		
Rapid Charge	Constant Current 1C5A Constant Voltage 3.65V		Charge time : Approx1.5h@≧10°C
	0.01C5A cut-off		
Standard discharge	Constant current 0.33C5A		16.5A
	end voltage 2.5 V Constant current: 2C5A		
Maximum discharge current	end voltage: 2.5 V		<u>100A@≧0°C</u>
Volumetric specific energy	295 WH/L		APPROX
Gravimetric specific energy	139WH/KG		APPROX
Battery Pack specifications			
Item	General Parameter 16S2P		Remark
Combination method			
Rated Capacity	Typical	100Ah	Standard discharge after Standard
	Minimum	98Ah	charge (package)
Factory Voltage	51V-53V(40-60%)		Mean Operation Voltage
Voltage at end of Discharge	40-44V 56-58V		Discharge Cut-off Voltage
Charging Voltage Internal Impedance	≪60mΩ		Internal resistance measured at AC 1KHZ after 50% charge The measure must uses the new batteries that within one week after shipment and cycles less than 5 times
Standard charge	Constant Current20A Constant Voltage see No.5 0.02CA cut-off		Charge time : Approx 6 h
Limiting current	20A		
Standard discharge	Constant current: 20A end voltage see NO.4		
Max Continuous Charge Curr			≥10°C
Max Continuous Discharge C 100A		≥10°C	
Operation Temperature Range	Charge(充电): 0~45℃ Discharge(放电): -20~55℃		60±25%R.H. Bare Cell
Storage Temperature Range	Less than 12 months : -10~35°C		60±25%R.H.
	less than 3 months: $-10~45^{\circ}$ C		at the shipment state
Dimonologo	Less than 7 day : -20~65°C		In aluda Dra aluat
Dimensions Woight	680*485*180 (220)mm Approx : 70kg		Include Bracket
Weight	Αμριοχ	; IUNY	l