

Electrical Characteristics

Module Type	M6-60-340	M6-60-345	M6-60-350
	STC	STC	STC
Maximum Power at STC (Pmp)	340	345	350
Open Circuit Voltage (Voc)	41.1	41.3	41.5
Short Circuit Current (Isc)	10.32	10.42	10.52
Maximum Power Voltage (Vmp)	34.7	34.9	35.1
Maximum Power Current (Imp)	9.80	9.89	9.97
Module Efficiency at STC(ηm)	20.0	20.4	20.7
Power Tolerance	(0,+4.99)		
Maximum System Voltage	1000 VDC		
Maximum Series Fuse Rating	20A		

STC: Irradiance 1000 W/m² module temperature 25°C AM=1.5;

Temperature Characteristics


Pmax Temperature Coefficient	-0.36 %/°C
Voc Temperature Coefficient	-0.28 %/°C
Isc Temperature Coefficient	+0.05 %/°C
Operating Temperature	-40~+85 °C
Nominal Operating Cell Temperature(NOCT)	45±2 °C
Fire Rating	Class C

Mechanical Specifications


External Dimensions	1690 x 1002 x 30 mm
Weight	19.0kg
Solar Cells	PERC Mono 158.75x79.375mm (120pcs)
Front Glass	3.2 mm AR coating tempered glass, low iron
Frame	Anodized aluminium alloy
Junction Box	IP68,3 diodes
Output Cables	4.0 mm ² ,Portrait:900mm or Customized Length
Connector	Genuine MC4 Connector /Compatible MC4 Connector
Mechanical Load	Front side 5400Pa/ Rear side 2400Pa

Packing Configuration

	1690 x 1002 x 30 mm
Container	40'HQ
Pieces per Pallet	36+36+7
Pallets per Container	13
Pieces per Container	1027




I-V Curve




Product Certificates



Warranty



Made in China



M6-60-340-350W