XPower DIGITAL

Mobile power for trucks, RVs, and boats

Available in:



Designed to power electronics while on the go, our new compact digital inverters combine innovative industrial design with an advanced interactive LED display. This provides the user with instant feedback on input current and output voltage, and valuable troubleshooting guidance through Fault Codes. These new digital inverters provide a convenient and powerful way to access AC power.

XPower Digital 400

- » 320 watts continuous power with 640 watts surge
- » Automatic shutdown protection against overload, over temperature and low/high battery conditions
- » DC terminals for a lighter socket or direct battery connection
- » Two, three-prong grounded AC outlets
- » 12 month warranty
- » Runs cell phone, camcorder, stereo, laptop computer, 20" TV/VCR combo, 27" TV



Applications:



Xantrex LLC

3700 Gilmore Way Burnaby, British Columbia Canada V5A 4B5 800 670 0707 Toll Free 604 420 1591 Fax

541 Roske Drive, Suite A Elkhart, Indiana USA 46516 800 446 6180 Toll Free 574 294 5989 Fax

www.xantrex.com



XPower DIGITAL



Electrical specifications	400	
Continuous AC output power	320 W	
5 minutes AC output power	400 W	
Maximum AC output surge power	700 W	
AC output voltage (nominal)	115 VAC	
AC output frequency	60 +/- 1 Hz	
AC output waveform	Modified sine wave	
Battery drain with no AC load (at 12V input)	0.25 A	
Efficiency (maximum)	90%	
DC input voltage range	10.5-15.5 VDC	
Low battery alarm trigger point (nominal)	11.0 V	
Low battery shut down point (nominal)	10.5 V	
High battery shut down point (nominal)	15.5 V	

General specifications

Ambient operating temperature range	0°C-40°C (32°F-104°F)
Dimensions (H x W x L)	9.25 x 3.64 x 6.68″
	(235x 92.68 x 169.72 mm)
Weight	2.2 lb (0.99 kg)
Warranty	12 months
DC connection	DC plug and battery clips
Part Number	813-0400-01

Packaging specifications		
Retail package size (H x W x L)	9.0 x 6.5 x 3.8"	
	(228.0 x 165.1 x 96.5 mm)	

2.4 lbs (1.0 kg)

Weight

Specifications are subject to change without notice. *Selectable range.