





xiom
SOLUTION S.A.

Exiom Solution diseña, fabrica y distribuye la más alta calidad en Energía Solar.

La alta eficiencia de nuestras células solares nos permite producir diferentes tipos de paneles para a su vez dar la mayor eficiencia posible a sus instalaciones.

Exiom Solution designs, manufactures and delivers high-performance solar electric technology worldwide. Our high-efficiency solar cell let us manufacture the different kinds of panels to get the most efficient in your installations.

**GARANTÍA DE RENDIMIENTO LINEAL
LINEAR PERFORMANCE WARRANTY**



25 AÑOS GARANTIA DE PRODUCTO / 25 YEARS PRODUCT WARRANTY

22.0
%

Extreme Power Production

The module efficiency up to 22.0% achieved by utilizing the most advanced technology in the solar industry.



SuperMBB Half-Cut Cell Technology

Using the advanced 9BB solar cell combines with half-cut cell technology to guarantee more power.



Advanced Bifacial Efficiency

Bifaciality >80%, effectively improves backside power generation. A bifacial cell design that generates energy from both sides, capturing and converting more sunlight into power even with a backsheet.



High Energy Yield

Excellent weak light performance and better performance in hot climate. Leading temperature coefficient for more production when the sun shines strongest, Or under the cloudy, haze condition.

5,400
2,400
Pascal



Guaranteed Better Durability

Certified for snow and wind loads of a maximum of 5,400 / 2,400 Pascals and with better protection against harsh weather to improve cell life for long-lasting high power.

Industry Leading Output Warranty

HTJ technology result in extremely low LID and PID which supports reliability and longevity. 12% power degradation in 30 years.

ELECTRICAL CHARACTERISTICS (STC*)

Maximum power - Pmax (W)	470	475	480	485	490
Open circuit current - Voc (V)	53.48	53.61	53.74	53.87	54.00
Short circuit current - Isc (A)	10.70	10.76	10.82	10.92	11.00
Voltage at maximum power - VMP (V)	45.66	45.86	46.08	46.28	46.48
Current at maximum power point - IMP (A)	10.30	10.36	10.43	10.48	10.54
Module efficiency (%)	21.6	21.9	22.1	22.3	22.5
Maximum System Voltage	1500Vdc (IEC / UL)				
Maximum Series Fuse	20A				
Max. power tolerance (%)	(0,+5)				
Bifaciality (%)	85±5				

BSTC**

Maximum power - Pmax (W)	520	525	530	535	540
Open circuit current - Voc (V)	55.33	55.93	56.53	57.13	57.73
Short circuit current - Isc (A)	11.61	11.65	11.69	11.73	11.77
Voltage at maximum power - VMP (V)	46.60	46.80	47.00	47.20	47.40
Current at maximum power point - IMP (A)	11.61	11.65	11.69	11.39	11.40


*STC: Irradiance 1000 W/m², module temperature 25°C, AM=1.5; Best in Class AAA solar simulator used, power measurement uncertainty is within +/- 3%.

**BSTC : Front side irradiation 1000W/m², back side reflection irradiation 135W/m², spectrum AM1.5, ambient temperature 25°C. Values are based on RETC certified results from a light-soaked module.

MECHANICAL PARAMETERS

Laminate Structure	Glass/ POE/ Cells/ POE/Glass
Cell Type	HJT Mono 166 x 83 mm
Cell Connection	144 (72x2)
Module Dimensions	2094x1038 mm
Weight	27 kg
Junction Box	IP68, 3 bypass diodes
Output Cable	4.0mm ² , 50cm (+), 50cm (-), length can be customized
Connectors Type	UV Resistant Cable/Compatible MC4
Frame	Anodised Aluminum
Front Load	5400 Pa
Real Load	2400 Pa
Glass Thickness	(F) 2.0mm Anti-reflective surface Solar glass (B) 2.0mm Solar glass

DRAWINGS



TEMPERATURE PARAMETERS

Nominal Operating Cell Temp. (NOCT)	45°C (±2°C)
Temperature Coefficient of Pmax	-0.24 %/°C
Temperature Coefficient of Voc	-0.22 %/°C
Temperature Coefficient of Isc	0.04 %/°C

PRODUCT CERTIFICATION

CERTIFIED
IEC
61730 Ed.1

CERTIFIED
IEC
61215 Ed.2

Anti-PID
System voltage durability
PPP 56042

