



Hunan Boltpower Storage Technologies Co.,Ltd.

Add:No.109, Building A, Lugu Science and Technology Innovation Park, changsha city, China
 Tel/Fax: 0086-731-85368837 Web:www.allsparkpower.cn
 Mob/WhatsApp: 0086-13786176622 Email:Jessica@allsparkpower.cn

Catalogue of Battery Pack

Mode	APB 2400	APB 3600	APB 4800
Picture			
Nominal Voltage(V)	48	48	48
Nominal Capacity(Wh)	2400	3600	4800
Usable Capacity(Wh)	2200	3200	4500
Dimension(mm)	442*410*100	442*420*150	442*420*177.5
Weight(Kg)	25	32	48
Discharge Voltage (V)	45 ~ 53.5	45~53.5	45~53.5
Charge Voltage(V)	52.5 ~ 53.5	52.5~53.5	52.5~53.5
Charge / Discharge Current (A)	25 (Recommended)	37 (Recommended)	50 (Recommended)
	50 (Max)	75 (Max)	100 (Max)
	100 (Peak@15s)	100 (Peak@15s)	100 (Peak@15s)
Communication Port	RS232 .RS485 .CAN	RS232 .RS485 .CAN	RS232 .RS485 .CAN
Single string quantity(pcs)	15	15	15
Working Temperature/℃	0~50	0~50	0~50
Shelf Temperature/℃	-20~60	-20~60	-20~60
Humidity	5%~85%	5%~85%	5%~85%
Altitude (m)	<2000	<2000	<2000
Design life	10+ Years (25 /77°F)	10+ Years (25 /77°F)	10+ Years (25 /77°F)
Cycle Life	>4000, 25℃	>4000, 25℃	>4000, 25℃
Authentication Level	CE / UN38.3	CE / UN38.3	CE / UN38.3
Agency quantity	100 pcs		
Packaging	Carton Box		
Warranty	5years		

Remark:**1) Validity of Price: 30 days, quotation date:.****2) Delivery time: in 30days less than 100 sets.****3) Term of Payment: T/T 30% prepaid + 70% after finished production.****4) MOQ:10 pcs**