

### KEY FEATURES



High module efficiency through superior manufacturing technology



No power loss thanks to improved temperature co-efficient caused by 11 busbar solar cell



Strictly control the micro-crack of solar cells and the other non visible defect of internal modules



Module can bear snow loads up to 5400Pa and wind loads up to 2400Pa



Manufactured according to and certified international I Quality and Environment Management System




Using advanced low reflection and high light transmission glass and cell sheet surface cutting technology, in the weak light environment can also play a good performance.

### CERTIFICATE

- IEC61215, IEC61730, CQC, CE, TUV
- ISO9001:2015
- ISO14001:2015
- ISO45001:2018



25 Years Power Output Warranty



### WARRANTY





Linear power output warranty  
 -12 years minimum 90.0% power output  
 -25 years minimum 80.2% power output




Product warranty on materials and workmanship  
 According to the applicable UKE Solar  
 Limited Warranty Statement





## IV-CURVES



## ELECTRICAL CHARACTERISTICS

Model	UKE530M10-72HB	UKE535M10-72HB	UKE540M10-72HB	UKE545M10-72HB
Maximum Power at STC(Pmax)	530W	535W	540W	545W
Optimum Operating Voltage (Vmp)	41.31V	41.51V	41.67V	41.83V
Optimum Operating Current (Imp)	12.83A	12.89A	12.96A	13.03A
Open-Circuit Voltage (Voc)	49.16V	49.36V	49.52V	49.68V
Short-Circuit Current (Isc)	13.72A	13.77A	13.84A	13.91A
Solar Module Efficiency (%)	20.5	20.7	20.9	21.1
Operating Temperature	-40to85°C			
Maximum System Voltage	DC1500V			
Maximum Series Fuse Rating	25A			
Power Tolerance	0~+3%			
STC:Irradiance 1000W/m <sup>2</sup> , Modules Temperature 25°C, AM=1.5				

## MECHANICAL CHARACTERISTICS

NOCT	43±2°C
Temperature Coefficient of Pmax	-0.35%/°C
Temperature Coefficient of VOC	-0.28%/°C
Temperature Coefficient of ISC	+0.048%/°C

## TEMPERATURE COEFFICIENTS

No.of cells	Mono PERC 182mm 144(6×12+6×12)
Dimensions	2279mm*1134mm*35mm
Weight	27.5kg
Front glass	3.2mm tempered glass
Frame	Anodized aluminum alloy
Junction box	IP68, three diodes
Connector	Plug and socket
Output cables	PV 4.0mm <sup>2</sup> , 0.3m
Packing Specification	31 pcs/Pallet, 155 pcs/ 20'GP; 620 pcs/ 40'HQ;

