


Ener-Wall W512135-L

Features



HeT | **ENERLIFE**

Shenzhen H&T Enerlife Technology Co., Ltd.

Add.: H&T Industrial Park, No.18 Baoshan Road, Tianliao Community, Guangming District, Shenzhen, China 518132

Tel.: +86 755 8611 1086 Email: enerlife@szhittech.com Web.: www.c-enerlife.com

Energize Your Life



Item	Parameter
Battery Type	LiFePO ₄
Nominal Capacity	135Ah
Nominal Energy	6.91kWh
Nominal Voltage	51.2V
Standard Charge Voltage	58.4V
Discharge Cut-off Voltage	44.8V
Max. Constant Charge Current	100A
Max. Constant Discharge Current	100A
Communication	RS485, CAN, WIFI (optional)
Configuration	Max. 16 in parallel
Ingress Protection	IP55
Operating Temperature ¹	-20~55°C/-4~131°F
Storage Temperature	-25~45°C/-13~113°F
Dimension(W*D*H)	1050*80*580mm
Weight	Approx. 70kg
Designed Life	≥ 10 years
Designed Cycle Life	≥ 6000 cycles
Certificates	UN38.3, CE

1. Performance will be derated at operating temperature below 10°C or above 45°C.