36 Cells Mono 25-190W



Electrical Characteristics STC*						
	Model	Pmax(W)	Vmp(V)	Imp(A)	Voc(V)	lsc(A)
	SESM1225	25	18.75	1.33	22.36	1.43
	SESM1230	30	18.85	1.59	22.43	1.70
	SESM1237	37	18.89	1.96	22.43	2.10
	SESM1240	40	18.90	2.12	22.46	2.26
	SESM1250	50	18.95	2.64	22.46	2.82
	SESM1260	60	19.00	3.16	22.54	3.38
	SESM1270	70	19.07	3.67	22.54	3.93
	SESM1274	74	19.10	3.87	22.54	4.15
	SESM1275	75	19.12	3.92	22.68	4.20
	SESM1280	80	19.15	4.18	22.68	4.47
	SESM12100	100	19.22	5.20	22.68	5.57
	SESM12120	120	19.28	6.22	22.68	6.66
	SESM12125	125	19.30	6.48	22.68	6.93
	SESM12150	150	18.00	8.35	22.50	9.00
	SESM12160	160	18.65	8.60	22.70	9.18
	SESM12170	170	19.15	8.90	23.38	9.35
	SESM12180	180	19.63	9.18	23.80	9.75
	SESM12190	190	20.33	9.35	24.13	9.95

STC (Irradiance 1,000W/m2, module temperature 25 , AM=1.5)





Temperature Characteristics					
	Nominal Operating Cell Temperature	45±2°C			
	Temperature Coefficient of Pmax	-0.42%/°C			
	Temperature Coefficient of Voc	-0.30%/°C			
	Temperature Coefficient of Isc	0.06%/°C			

SALIENT FEATURE OF OUR SOLAR PANELS

Wide Range	from	20	Watt to	340	Watt	*
J						

- Mono-crystalline Solar Cells used *
 - 12v, 24v ratings are available *
- High efficiency, resulting in high power output *
 - High Impact resistant toughened glass used 🜸
 - Custom design also undertaken 🔹

Maximum Ratings					
Operating Temperature range	-45°C ~+85°C				
Maximum system Voltage	600V				
Max series fuse rating	10A				
Max front load (e.g.: snow)	5400Pa				
Max back load (e.g.: wind)	2400Pa				

OUR PRODUCT



SOLAR PV MODULES

Our SPV modules from 20Wp modules to 340Wp modules, We curently mainain an active inventory of 20Wp, 40Wp, 50Wp, 80Wp, 100Wp, 250Wp, 300Wp, 320Wp, 325Wp SPV modules as per MNRE Specification.

SOLAR EPC

Our Goal is to install commercial and utillity scale photovltaic systeme which perform to the highest stanards and at maximum output.



SOLAR ROOF TOP SYSTEMS

Our quality products withstand the toughest environmental condition to provide the perfect solution for electricity generation. Solex PV Modules are made of highly efficient mono and poly crystalline solar cell which are resistant to rain, water, abrasion and hail impact.



SOLAR STREET LIGHTING

Solar street lights are powered by photovoltaic panels generally mounted on the lighting structure or integrated in the pole itself. The photovoltaic panels charge a battery, which powers LED lamps during the night. Street lights comes with dusk to dawn sensors, Which automatically on the light in evening and off in the morning and charging during the day.



SOLAR WATER PUMPING SYSTEMS

Solar Water Pumping system is a water lifting system powered by electricity generated by Solar panels. There are two types of Solar Water Pumps, one is Submersible Solar Pump and another is Surface Solar Pump. Both pumps are available in DC and AC.



SOLAR WATER HEATING SYSTEMS

Highly efficient water heating systems are being develoed by our research team to provide hot thoughout the year.



SOLAR POWERED PETROL STATIONS

Most petrol pumps require to be run on a 24x7 basis thereby requiring an intelligent Solar Power Management System. Alternate power sources like diesel generators have a higher switchover time and the dispenser pump shuts down almost instantly. Power fluctuations also end-up damaging dispensing units at petrol pumps. Sudden power failure leads to loss of fuel, time and money of both the customer and the petrol pump owner.

REG.OFFICE & WORKS SOLEX ENERGY LIMITED

 ⊕ www.solex.in ⋈ sales@solex.in | solexin14@gmail.com
◆ +91 2692 230317 | +91 93772 21443 1 +91 2692 231216
◆ PLOT NO -131 - A ,PHASE - 1, H.M. ROAD, GIDC, VITHAL UDYOGNAGAR-388121, ANAND, GUJARAT, INDIA.