




# FT-B Series Pure Sine Wave Inverter With Charger

(0.3KW、0.5KW、0.7KW、1KW)

## MAIN FEATURES

-  Pure sine wave output for compatibility with loads of different types
-  Visualization of operation status of the equipment through a digital LCD
-  A wide range of input voltage, accurate output and automatic voltage stabilization



## Product Specifications

Model: FT-B		0.3KW	0.5KW	0.7KW	0.7KW	1KW
Rated Power		300W	500W	700W	700W	1000W
Battery	Rated Voltage	12VDC/24VDC		24VDC	12VDC	12VDC/24VDC
	Voltage Range	73-138VAC/145-275VAC				
Input	Frequency	45-65Hz				
	Product Size: L*W*H(mm)	302*122*188			316*149*215	
	Package Size: L*W*H(mm)	375*195*260			410*215*280	
Output	Voltage Range	110VAC/220VAC; ±5%( Inversion mode)				
	Frequency	50/60Hz±1%( Inversion mode)				
	Output Wave	Pure Sine Wave				
	Conversion Time	<10ms(Typical load)				
	Efficiency	>85% (80% resistive load)				
	Overload	110-120%/30S; > 160%/300ms;				
	Protection Function	Battery overvoltage protection, battery undervoltage protection, overload, protection, short circuit protection, overtemperature protection, etc.				
	Operation Of Ambient Temperature	0-40°C				
Ambient Temperature For Storage	-15-+50°C					
Operation/Storage Ambient	0-90% No Condensation					

P.S.: We keep the right to change without any information.