

Lithium Series Dual 48V 5.1 kWh







MAXIMUM CUSTOMER SATISFACTION



PLUG & PLAY



PARALLEL/SERIES CONNECTION



TECHNICAL DATA

Model	Battery Lithium Series Dual 48V 5.1 kWh
Electrical	
Nominal Capacity	5.12 kWh
Usable Capacity	4.8 kWh
Depth of Discharge (DoD)	90 %
Nominal Voltage	51.2 V
Voltage operating range	48 – 56 V
Connection type	Series/Parallel
Cycle Life	>=6000
Physical	
Weight	45 kg
Dimensions	500 × 442 × 135 mm
Protection class	IP20
Battery type	LiFePO ⁴
Operation	
Maximum charge/discharge current	100 A (1 C)
Standard charge/discharge current	60 A (0,6 C)
Temperature operating range	0° C50° C
Humidity	< 60 %
Parallel Connection	
Number of batteries	8
Serial Connection	
Number of batteries	8
WiFi	
Monitoring System	Yes
APP	Yes
Remote Updating	Yes
BMS	
Monitoring parameters	System voltage and current, Cell voltage and temperature
Comunicación	Compatible CAN and RS-485



CAUTION: READ THE INSTRUCTION AND INSTALLATION MANUAL BEFORE USING THE PRODUCT ©Copyright 2020. All rights reserved. The specifications of the data sheet can be changed without prior notice.