

Stackable Lithium Iron Battery



Features

- Quality and safety are our lifelines, and the cells are only from the top five suppliers in China.
- Unique BMS technology: BYD vehicle-grade BMS technology is used in the field of energy storage, making it outstanding.
- 20 technological processes have strict inspection records, and quality inform ation can be traced.
- High life cycle, the design life is more than
 10 years, and the warranty is 5+5 years.
- Compatible with mainstream inverters, plug and play, host integrated combiner box.
- Support Bluetooth BT, expand power on demand and freely assemble, easy to install.
- Onesun has covered its battery with PICC (the People's Insurance Company of China).
- Stack up to 5 modules.



19











Product Parameters

Model	SUNIZE- B51.2V100AH	SUNIZE- B51.2V200AH	SUNIZE- B51.2V300AH	SUNIZE- B51.2V400AH	SUNIZE- B51.2V500AH	
Cell Type	LiFePO4					
Rated Capacity	100AH	200AH	300AH	400AH	500AH	
Minimum Capacity	98AH	196AH	296A	396AH	496AH	
Nominal Voltage	51.2V					
End-of-charge Voltage	58.0V±1.0V	V±1.0V 58 4V				
End-of-discharge Voltage	40.5V±2.0V	40.5V±2.0V 40.0V				
MAX Charge Current	100A	200A	300A	400A	500A	
MAX Continuous Discharge Current	100A	100A	150A	200A	250A	
MAX Instantaneous Discharge Current	100A±5A/1S	200A	300A	400A	500A	
Overcurrent Protection	120A±15A/100ms 120V					
Protection Function	OCVP / UVP / OCP / SCP / OTP etc.					
Communication Interface	RS485 / CAN					
Operating Temperature	Charging: 0°C~45°C Charging: 0°C~50°C Discharging: -10°C~60°C Discharging: -15°C~60°C					
Storage Temperature	-5°C~35°C					
Cycle Life	≥6000 Times @ 80% DoD					
Storage Humidity	≤75% RH					
Standard Environmental	Temperature: 25℃±2℃;Humidity: 45%~75%RH;Atmospheric Pressure: 86KPA~106KPA					
Charge Connector	Quick Connector	ick Connector M8 Terminal				
Discharge Connector	Quick Connector M8 Terminal					
Shell Meterial	Metal					
Shell Color	White					
Size	585*360*165mm	585*460*360mm	585*460*540mm	585*460*720mm	585*460*900mm	
Weight	Approx.42.4kg	Approx.92kg	Approx.138kg	Approx.184kg	Approx.240kg	

20

www.onesunpv.com www.onesunpv.com