

# Better Technology Group Limited

Compatible with 20+ mainstream brand of global inverter

Flexible stacking 10KWh/15KWh/20KWh/25KWh



Plug and Play



Driven 10KW Inverter



15 Layers of Protection



Master Integrated Combiner Box



Power Expansion  
Freely Assemble



Bluetooth (BT)



Easy Installation



LOGO Customization



[www.better-tech.net](http://www.better-tech.net)

## LiFePO4 Battery Brick

Battery Style	51.2V200Ah	51.2V300Ah	51.2V400Ah	51.2V500Ah
Nominal Voltage	51.2V			
Rated Capacity	200Ah	300Ah	400Ah	500Ah
End-of-charge Voltage	58.4V			
End-of-discharge Voltage	40.0V			
Standard Charge Current	100A	150A	200A	250A
Max. Charge Current	200A	300A	400A	500A
Standard Discharge Current	100A	150A	200A	250A
Max. Discharge Current	200A	300A	400A	500A
Max. Peak Current	300A	400A	500A	600A
Communication	RS485/CAN/BT			
Charge/Discharge Interface	M8 Terminal			
Communication Interface	RJ45			
Shell Material/Color	Metal/White			
Size	565*460*360mm	565*460*540mm	565*460*720mm	565*460*900mm
Weight	92kg (about)	138kg (about)	184kg (about)	240kg (about)
Work Temperature Range	Charge: 0°C-50°C Discharge: -15°C-60°C			

THE PARAMETERS ARE FOR REFERENCE ONLY. THE ACTUAL PRODUCT SHALL PREVAIL. SUPPORT CUSTOMIZATION AND ON-DEMAND CUSTOMIZATION.

[www.better-tech.net](http://www.better-tech.net)