

# 压载支架/SolaStrut SolarBallast II

## The Universal Non-Penetrating PV Mounting System



技术参数 Technical Features	
Installation Site	Flat roof
System Tilt Angle	20°
Wind load	41.7m/s
Snow load	70cm
Applicable Module	Framed
Module Orientation	Landscape
Standards	TUV IBC 2008
Bottom Material	SIKA Non-slip mat
Structure Material	Anodised aluminum
Service Life	25 years

支架特点 Key Benefits	
<b>安装方便 Easy Installation</b>	便携设计 成本低 Portable design makes the installation easily and cost effective.
<b>不破坏屋顶 Non-Penetrating</b>	采用压载不破坏屋顶 Combines the best of ballast to avoid the need for penetrating the roof with fasteners.
<b>良好的通用性 Great Compatibility</b>	这个设计与市场上的大多数组件边框匹配，具有良好的兼容性 Designed as a universal PV mounting system, SolaStrut SolarMatrix-I is compatible with most of the framed PV modules on the market.
<b>质量高 High Quality</b>	严格控制原材料和产品品质，保证产品的最大强度和寿命 Strict quality control over materials and finished products ensure optimum strength and long life for your installation.
<b>质保十年 10 Years Warranty</b>	Weihang Solar provides a 10 years product warranty for your peace of mind.

<p>WH-SB-SB</p> 	<p><b>压载短脚</b> SolarBallast Short Base</p> <ul style="list-style-type: none"> <li>○ Anodise aluminum</li> <li>○ AL6063</li> <li>○ Non-slip mat</li> </ul>	<p>WH-LB-SB</p> 	<p><b>压载长脚</b> SolarBallast Long Base</p> <ul style="list-style-type: none"> <li>○ Anodise aluminum</li> <li>○ AL6063</li> <li>○ Non-slip mat</li> </ul>
<p>WH-TF-SB</p> 	<p><b>三角架</b> SolarBallast Triangle Frame</p> <ul style="list-style-type: none"> <li>○ Highly Pre-assembly</li> <li>○ 20 degree triangle tilt</li> </ul>	<p>WH-FD-SB</p> 	<p><b>前防风板</b> SolarBallast Front Wind Deflector</p> <ul style="list-style-type: none"> <li>○ Galvanized iron plate</li> <li>○ Self-tapping screw</li> <li>○ Flat round head bolt</li> </ul>
<p>WH-SD-SB</p> 	<p><b>侧防风板</b> SolarBallast Side Wind Deflector</p> <ul style="list-style-type: none"> <li>○ Galvanized iron plate</li> <li>○ Self-tapping screw</li> <li>○ Flat round head bolt</li> </ul>	<p>WH-BD-SB</p> 	<p><b>后防风板</b> SolarBallast Back Wind Deflector</p> <ul style="list-style-type: none"> <li>○ Galvanized iron plate</li> <li>○ Self-tapping screw</li> <li>○ Flat round head bolt</li> </ul>
<p>WH-IC-SB</p> 	<p><b>中压</b> SolarBallast Inter Clamp</p> <ul style="list-style-type: none"> <li>○ Anodised aluminum</li> <li>○ M8 A2-70 Hex Socket Head Bolt</li> <li>○ 35,40,45,50mm</li> </ul>	<p>WH-ED-SB</p> 	<p><b>边压</b> SolarBallast End Clamp</p> <ul style="list-style-type: none"> <li>○ Anodised aluminum</li> <li>○ M8 A2-70 Hex Socket Head Bolt</li> <li>○ 35,40,45,50mm</li> </ul>