

## Energy Block HYBRID



### ADVANTAGES:

- PV input with 4 MPP trackers
- Back-up output (switching <20ms)
- Up to 100% three-phase unbalanced load
- Max. 120% back-up output overload for 60s
- Up to 110% mains-dependent output overload

HYBRID INVERTER GEN3	30kW-3P -3G-100	40kW-3P -3G-100	50kW-3P -3G-100	
Item number	672406	672408	672409	
<b>General data</b>				
Maximum efficiency	98,8			[%]
European efficiency	98,3			[%]
Noise development	<50			[dB]
Cooling	Internal fan			[-]
Weight	72			[kg]
Dimensions (WxHxD)	800 x 620 x 300			[mm]
Off-grid capable?	Yes			[-]
Switching time	<20			[ms]
Operating temperature min/max	-30/60			[°C]
Standby consumption	<15			[W]
Enclosure Protection class	IP65			[-]
Cascadable?	Yes, Eco: 10x Yes, Performance: 25x			[-]

<b>Battery*</b>				
Max. Charging/discharging current	100/100			[A]
Voltage range	135-850			[V]
Number of connections	1 plus, 1 minus			[-]
Battery type	LFP (lithium iron phosphate), 10-19 modules			[-]

<b>AC connection*</b>				
Nom. Output power	30	40	50	[kW]
Max. Peak power	33	44	55	[kW]
Max. Output current	50	66	83	[A]
Nom. Output voltage	400			[V]
Nom. Output frequency	50/60			[Hz]
Mains connection	3L/N/PE			[-]
Mesh type	TN network			[-]
Operating voltage	3P, 400V AC, 50Hz			[-]

<b>PV connection*</b>				
Number of PV MPPT	4 (with 2 string inputs each)			[-]
Recommended max. input power	45	60	75	[kW]
MPPT operating range	200-850			[V]
Max. Input current per MPPT	30 x 4			[A]
Max. Short-circuit current per MPPT	40 x 4			[A]
String connection per MPPT	2 (15A each)			[-]
Optimum MPPT operating voltage	620			[V]
Starting voltage	135			[V]
Max. DC input voltage	850			[V]

\* Performance reductions of up to 10% are possible.

All information without guarantee: Subject to typing and printing errors.

<b>BATTERY STORAGE</b>											
<b>Model</b>	<b>38.4</b>	<b>42.2</b>	<b>46.1</b>	<b>49.9</b>	<b>53.8</b>	<b>57.6</b>	<b>61.4</b>	<b>65.3</b>	<b>69.1</b>	<b>73.0</b>	
	<b>kWh</b>	<b>kWh</b>	<b>kWh</b>	<b>kWh</b>	<b>kWh</b>	<b>kWh</b>	<b>kWh</b>	<b>kWh</b>	<b>kWh</b>	<b>kWh</b>	<b>kWh</b>
<b>General data</b>											
Number of battery modules	10	11	12	13	14	15	16	17	18	19	[-]
Weight (without inverter)	480	572	614	656	698	740	782	824	866	908	[kg]
Dimensions (without inverter)	H	2000									[mm]
	B	600	1200								[mm]
	T	780									[mm]
Charging temperature range	0-40									[°C]	
Discharge temperature range	0-40									[°C]	
Enclosure Protection class	IP21									[-]	
Battery type	LFP (lithium iron phosphate)									[-]	
Number of cells per module	24									[-]	
Number of battery racks	1	2								[-]	
Certifications	UN38.3, IEC 62619:2022									[-]	
<b>Performance data</b>											
Number of battery modules	10	11	12	13	14	15	16	17	18	19	[-]
Max. Storage capacity	38,4	42,2	46,1	49,9	53,8	57,6	61,4	65,3	69,1	73,0	[kWh]
Nominal voltage	384	422	461	499	538	576	614	653	691	730	[V]
Max. Charging/discharging current	100 / 100									[A]	
Max. Discharge depth (DoD)	90									[%]	
Max. usable storage capacity***	34,6	38,0	41,5	44,9	48,4	51,8	55,3	58,8	62,2	65,7	[kWh]
Max. Charging efficiency	98,4									[%]	
Max. Discharge efficiency	97,5									[%]	


<b>Max. Charging/discharging power M-TEC Energy Block**</b>											<b>Inverter model</b>
Battery model	38.4	42.2	46.1	49.9	53.8	57.6	61.4	65.3	69.1	73.0	
	kWh										
Charging/discharging capacity [kW]	30										30kW-3P-3G-100
	38,4	40									40kW-3P-3G-100
	38,4	42,2	46,1	49,9	50						50kW-3P-3G-100

\*\* Table according to nominal values, deviation due to actual SoC and/or temperatures not taken into account!

\*\*\* Depth of discharge (DoD): 90%


<b>Integrated protective measures Hybrid inverter</b>
Reverse polarity protection for PV input, reverse polarity protection for battery input, insulation impedance protection, overvoltage protection, overtemperature protection, leakage current protection, anti-islanding protection, AC overvoltage protection, overload protection, short-circuit protection

### Hybrid inverter connections




- 3 PV switch
- 4 PV inputs
- 5 Battery input
- 6 Communication port COM1
- 7 Communication port COM2
- 8 Mains input
- 9 Back-up output
- 10 Communication port COM3
- 11 Generator input


### Battery connection



### Master BMS and sub-master BMS connections



**Electrical connection hybrid inverter**



**Overall system connection diagram (battery - EMS - inverter)**

