

## BMT-P2/144A(550W)

The GoodWe Polaris Series is designed to meet the needs of a variety of different applications. Whether installing it on a carport or sun shed, the Polaris Series is adaptable and versatile. One of the standout features of the Polaris Series is the availability of double-glazed tempered glass, which is resistant to high winds. Besides, the modular design and two installation options make it incredibly easy to install, saving time and hassle. Additionally, the integrated drainage structure ensures smooth and leak-free drainage. The Polaris Series also offers comprehensive performance advantages in safety, applicability, durability, economy, and environmental friendliness.



GOODWE

### High Impact Resistance

- 2+2mm Reinforced double-glazed glass
- Wind-resistant design
- Maximum static load on the front ≥ 5400Pa

## Fast Installation

- Modular design, easy replacement
- Two installation methods, accommodate sophisticated situation



Integrated Diverse Applications

• Carport

T

• Sun Shed



### Structured Integrated Drainage


- No need extra water guide
- Excellent waterproof sealing performance







# **POLARIS** Series



BMT-P2/144A

Structural Data	BMT-P2/144A
Size	2327x1160x30mm
Weight	32kg
Cell Type	182 Mono PERC
Electrical Data (STC) STC:AM=1.5, irradiance 100	0W/ $\rm m^2$ , Component Temperature 25° C
Max Power (Pmax)	550W
Voltage at Max Power (Vmpp)	41.35V
Current at Max Power (Impp)	13.30A
Voltage at Open Circuit (Voc)	49.84V
Current at Short Circuit (Isc)	14.18A
Module Efficiency	20.4%
Temperature Coefficient	
lsc	0.048%/°C
150	0.048%/C
Voc	-0.28%/°C
Voc	-0.28%/°C
Voc РМРР	-0.28%/°C
Voc PMPP Mechanical Load	-0.28%/℃ -0.35%/℃
Voc PMPP Mechanical Load Max Front Side Static Load	-0.28%/℃ -0.35%/℃ 5400Pa
Voc         PMPP         Mechanical Load         Max Front Side Static Load         Max Rear Side Static Load	-0.28%/℃ -0.35%/℃ 5400Pa
Voc PMPP Mechanical Load Max Front Side Static Load Max Rear Side Static Load Carbon Neutral Index (30 years)	-0.28%/°C -0.35%/°C 5400Pa 2400Pa
Voc   PMPP   Mechanical Load   Max Front Side Static Load   Max Rear Side Static Load   Carbon Neutral Index (30 years)   Energy Output	-0.28%/°C -0.35%/°C 5400Pa 2400Pa 16326kWh



PV Charging Carport With Storage



Various sheds

GOODWE