

TECHNICAL DATASHHET FIXED STRUCTURE





HIGH FLEXIBILITY The structures are adapted to

the client's requirements.



GREAT **ADAPTABILITY**

The design of the structures allows the absorption of high slopes in the terrain and a maximum use of the surface.



EASY ASSEMBLY

Structure designed with sufficient tolerances for easy assembly.



MINIMUN MAINTENANCE

Design and manufacturing components developed for minimal maintenance.

info@alphatracker.it www.alphatracker.it

FIXED STRUCTURE – GENERAL CARACTERISTICS

Superficial quality	HDG ZM310	FIXED STRUCTURE
fundation	Direct ramming Predrilling Micropile	
Screws	Zinc-Níquel, HDG Minimun 8.8 quality	
Modules fixing	Stainless Screws or Ribets	
Ground adaptance	High adaptability to the ground	
Tilt of modules	All Possibiliy	
Desing and calculation	Adapted to each client and location	
Configuration s	2P, 3P, 4P 2H, 3H According client requeriment	

TECHNICAL CARACTERISTICS

S355JR and S350GD

Material

Foundation N – S tolerance	± 30mm
Foundation E-O tolerance	± 50mm
Foundation vertical tolerance	± 20mm
Foundation inclination tolerance	± 1,5°

OPTIONAL SERVICES

- Assembly supervision
- Pull Out Test Supervision

WARRANTY

- 10 years of structure
- 25 years of corrosion



Sustainable design for a better future



info@alphatracker.it www.alphatracker.it