







Microinverter

IS-160/IS-180/IS-200

-  Safer with rapid shutdown compliance
-  Plug & Play, easy installation
-  4 MPPTs, 96.7%+ peak efficiency
-  WiFi integrated, direct communication with APP. Module level monitoring
-  IP67 protection, adapt to outdoor use
-  25 years design lifetime and 12 years warranty



Product Model	IS-160	IS-180	IS-200
Input Data (DC)			
Recommended PV Module Power (W)	(320~540+)*4	(360~600+)*4	(400~670+)*4
MPPT Voltage Range (V)	25~48		
Maximum Input Voltage (V)	60		
Startup Voltage (V)	22		
Maximum Input Current (A)	16*4	18*4	20*4
Maximum input short circuit current (ISC) (A)	25		
Number of MPPTs	4		
Output Data (AC)			
Rated Output Power (W)	1600	1800	2000
Rated Output Current (A)	6.96	7.83	8.70
Nominal Output Voltage (V)	220 / 230 / 240		
Nominal Output Frequency (Hz)	50 / 60		
Power Factor (Default / Adjustable)	0.99 / 0.90 leading...0.90 lagging		
Total Harmonic Distortion (THDi)	<3%		
Maximum units per branch	4	4	3
Efficiency			
Peak Efficiency	96.70%	96.70%	96.70%
Nominal MPPT Efficiency	99.80%		
Nighttime Power Consumption (mW)	<50		
Mechanical Data			
Operating Temperature Range (°C)	-40 ~ +65		
Storage Temperature Range (°C)	-40 ~ +85		
Altitude (m)	4000		
Noise (dB)	<20		
Enclosure Environmental Rating	IP67		
Cooling	Natural Cooling		
Dimensions (W*H*D mm)	340*286*39		
Weight (kg)	4.90		
Features			
Communication	WiFi / 2.4G		
Monitoring System	Inver Cloud		
APP	Inver Dealer / Inver Energy		
Warranty	12 Years		
Compliance	CE / VDE4105 / EN50549-1		