

ORISun N-Type OSD6DH7816H TOPCon High-Efficiency Dual Glass Solar Module With MBB Technology



Intelligent Manufacturing, High-Performance N-type Solar cell

Industry-leading intelligent and efficient production lines, with the highest quality standards in the industry. Ensuring the most cost-effective production.



Higher Yield

High power, low temperature coefficient, high bifaciality ensuring the product can generate more energy benefits even in cloudy or hot weather with the same area. The bifaciality power gain increases with the backside illumination which can reach up to 25% or more.



Extremely Durable

Thanks to the optimal material matching and interconnection encapsulation technology, the product has outstanding module weather resistance performances. The overall module has passed the certification of 2400Pa wind load and 5400Pa snow load, while minimizing the degradation caused by PID.




Guaranteed Reliability

Industry leading 30 year product and performance linear warranty. Adopting the most advanced N-type mass production technology to ensure low LID and LETID degradation.



Extremely Elegant


Simple and elegant industrial design, suitable for various application scenarios.




Mechanical Structure Specifications

Dimensions	2465 x 1134 x 30 mm / 97.1 x 44.7 x 1.2 in
Weight	34.6 kg / 76.3 lbs
Front Material	Tempered high transparency photovoltaic glass, 2.0 mm / 0.08 in, anti reflective film
Back Material	Semi tempered photovoltaic glass, 2.0 mm / 0.08 in,
Frame	Anodized aluminum alloy
Cell Type	156Half piece, N-type monocrystalline silicon bifacial TOPCon solar cells
Junction Box	Protection grade IP68
Cable	Wireway: 4 mm ² /TÜV, Length (+):300 mm/11.81 in & (-):200 mm

Packaging and Transportation



Transport by container or truck. For truck freight, each pallet has a loading capacity of 17.5 meters and a height of 3.5-4.5 meters.



Module Electrical Performance Specifications¹


Module model	Efficiency	Power*		Short-circuit current		Open circuit current		Optimal operating current		Optimum operating voltage	
	η [%]	Pmax [W]	STC	Isc [A]	NOCT	Voc [V]	NOCT	I _{mpp} [A]	NOCT	STC	V _{mpp} [V]
	STC²		NOCT³		STC		NOCT		STC		NOCT
635	22.72	478	635	11.52	14.27	52.91	55.69	10.74	13.39	44.50	47.41
640	22.90	482	640	11.58	14.34	53.05	55.84	10.78	13.45	44.69	47.59
645	23.07	486	645	11.64	14.42	53.13	55.93	10.82	13.49	44.92	47.81
650	23.25	490	650	11.71	14.51	53.20	56.00	10.84	13.55	45.20	47.97
655	23.43	494	655	11.77	14.58	53.35	56.16	10.87	13.57	45.43	48.28

* (Power tolerance 0 W / +5 W for STC)

Bifacial Power Generation Performance (Rearside gain)

	Pmax	667Wp	672Wp	677Wp	683Wp	688Wp
5%	Efficiency	23.85%	24.04%	24.23%	24.42%	24.60%
15%	Pmax	730Wp	736Wp	742Wp	748Wp	753Wp
	Efficiency	26.12%	26.33%	26.54%	26.74%	26.95%
25%	Pmax	794Wp	800Wp	806Wp	813Wp	819Wp
	Efficiency	28.40%	28.62%	28.84%	29.07%	29.29%

I-V Curve Under Different Illuminances



System Related Technical Parameters

Maximum system voltage	[V]	1500
Maximum rated fuse current	[A]	30
Security level		II
Fire rating(UL61730)		I
Operating temperature range	[°C]	-40 to +85
Reference bifacial factor	[%]	80±5

Related Certifications

IEC IEC 61215:2016, IEC 61730:2016, UL 61730-1, UL 61730-2, PID (IEC 62804), Salt Mist (IEC 61701)


Note: All data and specifications are preliminary and may change without notice. For installation and operation instructions, please refer to the installation guide.

Temperature Coefficient

Isc TEMP coefficient	α	[%/K]	+0.045
Voc TEMP coefficient	β	[%/K]	-0.25
P _{mpp} TEMP coefficient	γ	[%/K]	-0.29
Nominal operating TEMP	NOCT	[°C]	45±2

The temperature coefficient described is a linear value.

Industry Leading Linear Quality Assurance



Passed Multiple IEC Standards With 3x Reliability And Weather Resistance Testing Procedures

1x IEC	Average Standard
3x IEC	The Lowest Testing Level Of Orisolartech

¹ Power test according to IEC 60904-3, test tolerance: 0~+3%

² STC condition: Light intensity 1000 W/m², Component temperature 25 °C, AM1.5G spectral conditions

³ NMOT: nominal component operating temperature, light intensity 800 W/m², AM1.5G spectral conditions, ambient temperature 20 °C