



Crystal **N8**

Black Thru Mono-Crystalline **430~450W**

0~+5W POWER TOLERANCE

- High efficiency N - type Black Grid Double Glass Module
- Stronger properties, PID resistance, reduced hot spot loss
- Better temperature coefficient
- Harsh environmental adaptation
- Black transparent module, aesthetic appearance
- Bifacial module, more power generation

25 years product warranty 

30 years power linear warranty 



22.5%
MAXIMUM CONVERSION

0~+5W
POWER TOLERANCE


0.4%
0.4% PER YEAR OVER 30 YEARS

Half-Cut Module
LOWER TEMPERATURE COEFFICIENT

Specification

Cell Type	Mono Crystalline 16BB
No. of Cells	108 [2x(6x9)] pcs
Dimension	1762×1134×30mm
Weight	25kg±3%
Front Glass	2.0mm
Back Glass	2.0mm
Frame	Black Anodized Aluminum Alloy
Junction Box	IP68
Cable Length	300mm,1200mm(can be customized)

Mechanical Diagrams



Length: ±2mm Width: ±2mm Thickness: ±1mm Hole pitch: ±2mm

Packing Standard

36pcs/pallet

40HQ: 26 pallets/container, 936pcs/container

Electrical Parameters At STC

Module Type	QN-430HD-1	QN-435HD-1	QN-440HD-1	QN-445HD-1	QN-450HD-1
Peak Power-Pmax (W)	430	435	440	445	450
Open Circuit Voltage-Voc (V)	39.53	39.75	39.96	40.17	40.38
Short Circuit Current-Isc (A)	13.57	13.58	13.79	13.86	13.94
Maximum Power Voltage-Vmp(V)	33.11	33.34	33.58	33.81	34.06
Maximum Power Current-mp(A)	13.00	13.04	13.10	13.16	13.21
Module Efficiency - nm(%)	21.5	21.8	22.0	22.3	22.5

Electrical Parameters At NOCT

	325	329	333	336	340
Maximum Power-Pmax(W)					
Open Circuit Voltage-Voc (V)	37.55	38.02	37.43	37.62	37.91
Short Circuit Current-Isc (A)	10.86	10.86	11.03	11.09	11.15
Maximum Power Voltage-Vmp (V)	31.04	31.31	31.74	31.95	32.19
Maximum Power Current-Imp (A)	10.47	10.50	10.48	10.53	10.57

Operating Parameters




Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	25A
Nominal Operating Cell Temperature	42±2°C
Operational Temperature	-45°C~+85°C
Safety Class	Class II

Temperature Coefficient (STC Test)

Temperature Coefficient of Isc	+0.04%/°C
Temperature Coefficient of Voc	-0.24%/°C
Temperature Coefficient of Pmax	-0.29%/°C

Load Capacity

Max Load Front	5400Pa
Max Load Back	2400Pa
Through Hail Testing	25mm Diameter, Impact Speed 23m/s



STC: Irradiance:1000W/m² | Battery temperature: 25°C | Atmospheric=1.5

NOCT: Irradiance:800W/m² | Ambien temperature: 20°C | Atmospheric=1.5 | Wind speed 1m/s

D5 Greenland Window Building
Nonghua Road
Yuhuatai District, Nanjing, China
www.q-sunsolar.com

