

Haitai TaiHe2.0 (182)

HTM615~635DMH5-78NT TOPCon Bifacial high efficiency PV module

22.72%

Module Efficiency 22.72%

PRODUCT FEATURES

High Power Output
N-type MBB half cut technology, improve energy density, bring higher power output.
High Bifacial Factor, up to 25% extra power generation

High Durability
Passed TUV Salt & Ammonia corrosion test, and 2400Pa wind load, 5400Pa snow load test, higher reliability


Better Low Light Performance
Higher power generation compare with standard module in cloudy, foggy and low light condition

Low Power Degradation
First year power degradation <1.0%, year 2-30 power degradation <0.40% each year

Low Temperature coefficient
Passivated contact cell technology for higher power generation in operating

Better Anti-LID
N-type cells with boron-oxide-free composite LID to increase module power generation

LINEAR PERFORMANCE WARRANTY



12 YEARS product warranty

30 YEARS linear power warranty

0.40% Linear attenuation of 0.40% per year within 30 years

CERTIFICATES

- IEC 61215, IEC 61730
- ISO 9001: 2015 Quality Management System
- ISO 14001: 2015 Environment Management System
- ISO 45001: 2018 Occupational health and safety management systems



Electrical Data (STC)

Maximum Power (Pmax/W)	615	620	625	630	635
Open Circuit Voltage (Voc/V)	55.31	55.46	55.61	55.76	55.91
Short Circuit Current (Isc/A)	13.9	13.98	14.05	14.13	14.2
Voltage at Maximum Power (Vmp/V)	45.78	45.93	46.08	46.23	46.38
Current at Maximum Power (Imp/A)	13.44	13.51	13.57	13.63	13.7
Module Efficiency (%)	22.00	22.18	22.36	22.54	22.72
Operating Temperature	-40° C~+85° C				
Maximum System Voltage	1000/1500V				
STC (Standard Testing Conditions): Irradiance 1000W/m ² , Cell Temperature 25° C, AM1.5					

Electrical Data (NMOT)

Maximum Power (Pmax/W)	462	466	470	474	478
Open Circuit Voltage (Voc/V)	52.58	52.73	52.88	53.03	53.18
Short Circuit Current (Isc/A)	11.34	11.41	11.47	11.54	11.6
Voltage at Maximum Power (Vmp/V)	43.03	43.18	43.33	43.48	43.63
Current at Maximum Power (Imp/A)	10.74	10.8	10.85	10.91	10.96

NMOT (Nominal Module Operating Temperature): Irradiance 800W/m², Ambient Temperature 20° C, AM1.5, Wind Speed 1m/s.

Bifacial Power Generation Parameters (Backside Gains)

5%	Maximum Power (Pmax/W)	646	651	656	662	667
	Module Efficiency (%)	23.10	23.29	23.48	23.66	23.85
15%	Maximum Power (Pmax/W)	707	713	719	725	730
	Module Efficiency (%)	25.30	25.51	25.71	25.92	26.12
25%	Maximum Power (Pmax/W)	769	775	781	788	794
	Module Efficiency (%)	27.50	27.73	27.95	28.17	28.40

Mechanical Data

Cell Type	182×91mm Mono
Cell Orientation	156(6×26)
Module Dimensions	2465×1134×30mm
Weight	34.5kg
Glass	2.0mm high transmittance, reinforced glass
Backsheet	2.0mm part of the structure is grid-like white ceramic glass
Frame Material	Anodized aluminum alloy
Junction Box	Protection class IP68
Cable	4.0 mm ² positive pole: 200 mm negative pole: 250 mm wire length can be customized
Connector	MC4 compatible connector


Temperature Coefficients

Temperature Coefficient (Pm)	-0.300%/°C
Temperature Coefficient (Voc)	-0.250%/°C
Temperature Coefficient (Isc)	0.046%/°C
NMOT (Nominal Module Operating Temperature)	41±3° C

Packaging

Transportation methods	Number of modules per cabinet	Number of modules per pallet
40HQ container	576pcs	36pcs +36pcs

Module Dimensions (mm)



I-V Curve

