



OPzS Battery



OPzS series is a traditional tubular plate flooded battery which offers 25+ years design life according to the standard IEC60896-11. With a new design and technical improvement, it offers maximum efficiency and reliability for the widest variety of applications. This series is highly suited for all standby power applications that require the highest levels and security.

Model	Voltage (V)	Capacity (10HR/Ah)	Dimension (mm)				Weight (Kg)	
			Length	Width	Height	Total Height	Dry weight	Wet weight
OPzS2-200	2	200	103	206	355	399	12.80	17.50
OPzS2-250	2	250	124	206	355	399	15.10	20.50
OPzS2-300	2	300	145	206	355	399	17.50	24.00
OPzS2-350	2	350	124	206	471	512	19.80	27.00
OPzS2-420	2	420	145	206	471	512	23.00	32.00
OPzS2-490	2	490	166	206	471	512	26.20	38.00
OPzS2-600	2	600	145	206	647	688	32.50	47.00
OPzS2-800	2	800	191	210	647	688	45.00	64.00
OPzS2-1000	2	1000	233	210	647	688	53.90	78.00
OPzS2-1200	2	1200	275	210	647	688	64.00	92.00
OPzS2-1500	2	1500	275	210	797	838	77.00	112.00
OPzS2-2000	2	2000	397	212	772	813	119.50	150.00
OPzS2-2500	2	2500	487	212	772	847	150.00	204.00
OPzS2-3000	2	3000	576	212	772	813	170.00	230.00