

# Rack Mounted Battery Module

**BMR series**



## RACK MOUNTED BATTERY MODULE

BMR series Battery Modules are high-performance, scalable, battery storage solutions. The built-in intelligent BMS can protect the battery pack and extend its service life. The modular design allows for flexibility, making it suitable for a broad range of storage applications.

For More about SVC range of products, visit: [www.svcenergy.com](http://www.svcenergy.com)

## MAIN FEATURES

- ▶ Cells cycle times 6000 cycles(+25°C 0.2C 80% DOD).
- ▶ Long lifespan: 5 years warranty, 10 years life design.
- ▶ 3U/4U rack-mount chassis design is easy for parallel expansion and maintenance.
- ▶ Smart BMS system to optimize the performance.
- ▶ Communication: RS485/SNMP/Wifi/Bluetooth, Compatible with different brand of solar inverter and chargers.
- ▶ All around protection: such as SOC/SOH etc..
- ▶ High discharge rate currents, suitable for on-grid or off-grid solar system and other loads.
- ▶ Maximum of 16 battery packs can be connected in parallel.
- ▶ With front display to know effectively the status of the batteries.

## Technical Parameter

Model	LFP24-100	LFP48-100	LFP48-200
<b>SPECIFICATION</b>			
Battery Type	LiFePO4	LiFePO4	LiFePO4
Battery Model	25.6V100AH	51.2V100AH	51.2V200AH
Nominal Capacity(25°C, 0.2C)WH	2560Wh	5120Wh	10240Wh
Adjustable working voltage(Vdc)	20 ~ 29.2V	40 ~ 58.4V	40 ~ 58.4V
Float Charge Voltage(Vdc)	28V	56V	56V
Max.Continuous discharge current(A)	100	100	100
Max.pulse discharge current(A)	150A(1 sec) configurable		
Max.Continuous charge current(A)	100		
Cycle life(+25°C 0.2C 80% DOD)	> 6000 Cycles		
Cell Equalizer Current(A)	0.1 ~ 5A Max.(optional)		
Terminal	Up to 16pcs		
Storage duration	6 months at 25°C		
Safety standard	IEC62619,UN38.3,MSDS,CE		
Communication function	RS485/CAN/RS232(Standard), SNMP/Wifi/Bluetooth/Dry Contact (optional)		
Communicate with mainstream inverter	Growatt/Voltronic/GOODWE/Pylontech/Kstar/MUST etc.		
<b>PROTECTION</b>			
Protection	Overcharge protection\Overdischarge protection\Overcurrent protection\Shortcircuit protection\Overtemperature protection		
<b>AMBIENT</b>			
Noise(dB)	< 40dB(1 meter)		
Working temperature	-20°C ~ +60°C		
Humidity	0~ 95%(no condensation)		
Altitude(m)	<3000		
<b>DIMENSION</b>			
L*W*H(product size)mm	L444*W483*H178	L665*W483*H178	L810*W483*H178
L*W*H(package size)mm	L523*W495*H243	L770*W523*H243	L920*W523*H243
Net Weight(Kg)	27.1	47.8	79.3
Gross Weight(Kg)	28.9	49.8	82.6

Additional Features (optional feature) LCD Display

Product specifications are subject to change without notice.