



485-515W

n-type Bifacial Dual-Glass **Transparent Black** Module

J-TOPCon
Technology

KODAK SOLAR MODULE 485-515W FBBI AM+ PPE2

515W

Maximum Power Output

23.2%

Maximum Module Efficiency

0~+3%

Power Output Tolerance



10-30% Additional Power Generation

30 years lifespan brings 10-30% additional power generation comparing with conventional P-type module.



Better Weak Illumination Response

Higher power output even under low-light environments like on cloudy or foggy days.



ZERO LID (Light Induced Degradation)

n-type solar cell has no LID naturally which can increase power generation.



Better Temperature Coefficient

Lower temperature coefficient (-0.28%) and lower working temperature, resulting in more power.



Higher Reliability

New generation TOPCon technology for the cell. No polysilicon wrap around, no current leakage, and greater resistance to hot spots.




Wider Applicability

More application scenes like BIPV, vertical installation, snowfield, high-humid, windy and dusty area.



IEC 61215(2021)/IEC 61730(2023)/IEC 61701/IEC 62716
ISO 9001:2015: Quality Management System
ISO 14001:2015: Environment Management System
ISO 45001:2018: Occupational health and safety
IEC 62941:2019: Quality system for PV module manufacturing

Linear Performance Warranty



25 Years Product Material & Workmanship / 30 Years Linear Performance Warranty



485-515W FBBI AM+ PPE2 | n-type Bifacial Dual-Glass Transparent Black Module

Electrical Properties | STC*

Testing Condition	Front Side	Front Side	Front Side	Front Side	Front Side	Front Side	Front Side
Peak Power (P _{max}) (W)	485	490	495	500	505	510	515
MPP Voltage (V _{mp}) (V)	32.96	33.14	33.32	33.50	33.68	33.86	34.04
MPP Current (I _{mp}) (A)	14.71	14.78	14.85	14.92	14.99	15.06	15.13
Open Circuit Voltage (V _{oc}) (V)	38.43	38.63	38.83	39.03	39.23	39.43	39.63
Short Circuit Current (I _{sc}) (A)	15.60	15.66	15.72	15.78	15.84	15.90	15.96
Module Efficiency (%)	21.8	22.0	22.3	22.5	22.7	22.9	23.2

*STC: Irradiance 1000 W/m², Cell Temperature 25°C, AM1.5
The data above is for reference only and the actual data is in accordance with the practical testing Power Measurement Tolerance ±3%

Electrical Properties | NMOT*

Testing Condition	Front Side	Front Side	Front Side	Front Side	Front Side	Front Side	Front Side
Peak Power (P _{max}) (W)	363	367	371	375	378	382	386
MPP Voltage (V _{mp}) (V)	31.56	31.73	31.91	32.08	32.25	32.42	32.60
MPP Current (I _{mp}) (A)	11.51	11.57	11.62	11.67	11.73	11.78	11.83
Open Circuit Voltage (V _{oc}) (V)	36.79	36.99	37.18	37.37	37.56	37.75	37.94
Short Circuit Current (I _{sc}) (A)	12.60	12.65	12.70	12.75	12.80	12.84	12.89

*NMOT: Irradiance 800 W/m², Ambient Temperature 20°C, Wind Speed 1 m/s

Electrical Properties Under Different Rear Gain | 500w

Power Gain (%)	Peak Power (P _{max}) (W)	MPP Voltage (V _{mp}) (V)	MPP Current (I _{mp}) (A)	Open Circuit Voltage (V _{oc}) (V)	Short Circuit Current (I _{sc}) (A)
10	550	33.50	16.42	39.03	17.36
15	575	33.50	17.16	39.03	18.15
20	600	33.60	17.86	39.13	18.89
25	625	33.60	18.60	39.13	19.68
30	650	33.60	19.35	39.13	20.47

Operating Properties

Operating Temperature (°C)	-40°C~+85°C
Maximum System Voltage (V)	1500V DC (IEC)
Maximum Series Fuse Rating (A)	35A
Bifaciality*	80%
Static Load	Front side 5400Pa, Rear side 2400Pa

*Bifaciality = P_{max}rear (STC) / P_{max}front (STC), Bifaciality tolerance: ±5%


Temperature Coefficient

Temperature Coefficient of P _{max}	-0.280%/°C
Temperature Coefficient of V _{oc}	-0.250%/°C
Temperature Coefficient of I _{sc}	+0.045%/°C
Nominal Operating Cell Temperature	45±2°C


Mechanical Properties

Number of Cells	108pcs
Module Dimension	1960mm*1134mm*30mm
Weight	27.3kg
Front / Rear Glass	2.0mm/2.0mm Heat-strengthened glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 (3 diodes)
Length of Cable	4.0mm ² , +1300mm/-1300mm (Cable length can be customized)
Packaging Configuration	37pcs/Pallet, 888pcs/40'HQ


Engineering Drawing (unit: mm)



Characteristic Curves 500w



I-V Characteristics At Different Irradiations



P-V Characteristics At Different Irradiations