

# 40MWh-8MW

## 8 pieces of 5MWh

Lingtech Liquid Cooled Energy Storage System



### OPTIMAL COST

- Intelligent Lingtech liquid-cooled temperature control system to optimize the auxiliary power consumption
- Pre-assembled, no battery module handling on site, transportation of complete system



### EFFICIENT AND FLEXIBLE

- High-efficiency heat dissipation, increase battery life and system discharge capacity
- Front single-door-open design, supporting back to back layout drawing
- Function test in factory, limited on-site work, accelerate commissioning process



### SAFETY AND RELIABLE

- Electrical safety management, overcurrent fast breaking and arc extinguishing protection
- The electrical cabinet and battery cabinet are separated to prevent thermal runaway



### CONVENIENT O&M

- One-click system upgrade
- Automatic coolant refilling design
- Online intelligent monitoring  
Remote maintenance

Technical Data	LT5015kWh
<b>DC side</b>	
Cell type	LFP 3.2 V / 314 Ah C-rate:0.5C
Battery configuration	416S12P
Nominal capacity	5015 kWh
Nominal voltage range	1123.2 V - 1497.6 V
<b>AC side</b>	
Nominal AC power	8MW in total
AC current distortion rate	< 3 % ( Nominal Power )
DC component	< 0.5 %
Nominal AC voltage	400V-690 V
AC voltage range	621 V - 759 V
Termination (LV)	3 phase
Power factor	> 0.99 ( Nominal Power )
Adjustable range of reactive power	- 100 % - 100 %
Nominal frequency	50 /60Hz
Isolation method	Transformerless
<b>System parameter</b>	
Dimension ( W * H * D )	6058 mm * 2896 mm * 2438 mm
Weight	42000 kg
Degree of protection	IP55
Anti-corrosion Degree	C3
Operation Ambient Temperature Range	- 30 °C - 50 °C ( > 45 °C Derating )
Operation humidity range	0 % - 100 % ( Non-condensing )
Maximum Operation Altitude	4000 m
Temperature Control Method	Intelligent Liquid Cooling
Fire suppression system	FACP, FK5112, Flammable gas detector, Smoke detector, Heat detector, Sounder beacon, Alarm bell, Warning sign, Extinguishant abort button, Ventilation system, Pressure relief port, Manual automatic switching and emergency starting device(Default) Sprinkler, Vent panel, Aerosol ( Optional )
Communication	Ethernet/Modbus TCP,IEC104
IEC61000, IEC62619, IEC62933,UN38.3,CE,IEC62477	