




**Tier1**

BloombergNEF  
Power the future

# TOPCon 182 BIFACIAL 485-500W

· Black frame, Bifacial Transparent




 UTILITY

 C&I

Module efficiency

# 23.08%



## WARRANTY

Quality Guarantee **25** years

Power Warranty **30** years

## CERTIFICATE



Ariet Green



## ELECTRIC CHARACTERISTICS

## SPDG (485/500W)-N120M10

Model of modules	SPDG485-N120M10		SPDG490-N120M10		SPDG495-N120M10		SPDG500-N120M10	
	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Power (Pmax/W)	485	363.00	490	366.00	495	369.9	500	373.8
Maximum power voltage (Vmp)	35.52	33.20	35.66	33.30	35.80	33.4	35.94	33.6
Maximum power current (Imp)	13.66	10.92	13.75	11.00	13.83	11.07	13.92	11.14
Open circuit voltage (Voc)	42.94	40.20	43.06	40.30	43.21	40.5	43.36	40.6
Short circuit current (Isc)	14.38	11.59	14.47	11.66	14.56	11.73	14.65	11.8
Module efficiency	22.39%		22.62%		22.85%		23.08%	

STC (Electrical parameters at standard test conditions. STC:AM=1.5, 1000W/m<sup>2</sup>, Cells Temperature 25°C)

NMOT (Irradiance 800W/m<sup>2</sup>, Ambient Temperature 20°C, AM1.5, Wind Speed 1m/s)

## ELECTRICAL CHARACTERISTICS WITH 15% REAR SIDE POWER GAIN

Front power Pmax/W	557.75	563.50	569.25	575.00
Maximum power voltage (Vmp)	35.52	35.66	35.80	35.94
Maximum power current (Imp)	15.70	15.80	15.90	16.00
Open circuit voltage (Voc)	42.94	43.06	43.21	43.36
Short circuit current (Isc)	16.54	16.64	16.74	16.85

## STRUCTURAL CHARACTERISTICS

Module size (L*W*H)	1910x1134x35mm
Weight	26kg
Cell	120 cells, N type Mono-Crystalline, 182mm×91mm
Front glass	2.0mm, Anti-Reflection Coating
Back glass	2.0mm, Heat Strengthened Glass
Frame	Anodized aluminum alloy
Junction box	IP68, 3 bypass diodes
Output wire	4mm <sup>2</sup>
Wire length	Line length 1100mm/customized
Connector	MC4 Compatible
Packing Specification	31 pcs/Pallet; 744pcs/40' HQ


## OPERATING PARAMETERS

Power tolerance (W)	(0~+5W)
Maximum system voltage (V)	1500V
Maximum rated fuse current (A)	30A
Current operating temperature (C)	-40~+85°C
Mechanical load	+5400Pa/-2400Pa


## TEMPERATURE CHARACTERISTICS

Temp. Coeff. of Isc (TK Isc)	0.046% / °C
Temp. Coeff. of Voc (TK Voc)	-0.25% / °C
Temp. Coeff. of Pmax (TK Pmax)	-0.30% / °C
Normal Operating Cell Temperature	45±2°C

## MODULE DIMENSIONS(MM)



## I-V CHARACTERISTICS AT DIFFERENT IRRADIATION



### Zhejiang Sunpro Power Technology Co., Ltd

Add: Qinggang Industrial Zone, Yuhuan City, Zhejiang Province

Tel: +86 0576-80730906 E-mail: info@sunpropower.com Website: www.sunpropower.com

\*The above parameters are for reference only, and the actual parameters of the factory shall prevail