



Goosun Energy Construction Group Co., Ltd



605W~630W

N-Type Monocrystalline Bifacial Solar Modules

▶ Product Characteristics

N-Type Technology

The N-Type module has lower LID/LeTID attenuation and better low light performance.

multi-master grid technology

Better light utilization and current harvesting capability. Effectively improves product power output and reliability.

12 Year

Material Workmanship Warranties

load capacity

Integral assembly passes frontal maximum test static at 6000 Pa. load certification.

Anti PID Guarantee

Through the optimization of battery production technology and material control to minimize the chance of degradation caused by PID phenomenon.

30 Year

The nature of the year line protects

double-sided generation

Increased light exposure on the back side of double-sided power generation significantly reduces LCOE

HOT 3.0 Technology


HOT3.0 technology N-type modules offer better reliability and power generation efficiency.

1 %

First year power degradation

0.4 %

Linear power attenuation



▶ certification

- EC61215、IEC61730、CE、CQC
- ISO8001:2015 Quality Management System
- 18014001:2015 Environmental Management System
- ISO45001:2018 Occupational Health and safety management



605~630W N-type monocrystalline silicon bifacial solar modules

Mechanical Characteristics

Cell Type	N- type Mono-crystalline
No. of cells	132 (66×2)
Dimensions	2382×1134×30 mm
Weight	32.4 kg
Front Glass	2.0 mm, Anti-reflection Coating
Back Glass	2.0 mm, Heat Strengthened Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68 Rated
Protection Class	Class II
IEC Fire Type	Class C
Connector Type	JK03M/MC4/Others
Output Cables	4.0 mm ² (+): 400 mm , (-): 200 mm or Customized Length

Packaging Configuration

Pallet Dimentions	2396×1110×1251 mm
Packing Detail (Two pallets = One stack)	13m flatbed: 36/pallet, 20/pallet, 720/pallet 17.5m flatbed: 36/pallet, 25/pallet, 900/pallet

Specifications(STC)

Maximum Power - Pmax [Wp]	605	610	615	620	625	630
Maximum Power Voltage - Vmp [V]	40.31	40.46	40.60	40.74	40.88	41.02
Maximum Power Current - Imp [A]	15.01	15.08	15.15	15.22	15.29	15.36
Open-circuit Voltage - Voc [V]	48.48	48.68	48.88	49.08	49.28	49.48
Short-circuit Current - Isc [A]	15.90	15.96	16.02	16.08	16.14	16.20
Module Efficiency STC [%]	22.4	22.6	22.8	23.0	23.1	23.3
Power Tolerance	0 ~ +3 %					
Temperature Coefficients of Pmax	-0.29 %/°C					
Temperature Coefficients of Voc	-0.25 %/°C					
Temperature Coefficients of Isc	0.045 %/°C					

STC: Irradiance 1000W/m², Cell Temperature 25°C, AM=1.5

Specifications(BNPI)


Maximum Power - Pmax [Wp]	668	674	679	685	690	696
Maximum Power Voltage - Vmp [V]	40.29	40.46	40.59	40.75	40.88	41.04
Maximum Power Current - Imp [A]	16.58	16.66	16.73	16.81	16.88	16.95
Open-circuit Voltage - Voc [V]	48.46	48.66	48.86	49.06	49.26	49.46
Short-circuit Current - Isc [A]	17.56	17.64	17.70	17.77	17.83	17.90

BNPI: Irradiance: front 1000W/m², rear 135W/m², Cell Temperature 25°C, AM=1.5

Application Conditions

Operating Temperature	-40 °C ~ +70 °C
Maximum System Voltage	1500 VDC (IEC)
Maximum Series Fuse Rating	35 A
Bifaciality Coefficient	φVoc: 98±5 %, φIsc: 80±5 %, φPmax: 80±5 %


Engineering Drawings




*Note: For specific dimensions and tolerance ranges, please refer to the corresponding detailed module drawings.

Electrical Performance

Current-Voltage Curves 625W



Current-Voltage Curves 625W



Goosun Energy Construction Group Co., Ltd

www.guochengsolar.

605~630W
N-type monocrystalline silicon bifacial solar modules