

Scopio-P

Outdoor Commercial and Industrial Energy Storage Scopio Series

Scopio AS100k-500k-01

Scopio AS100k-500k-01
Technical parameters



Automatic
Grid/Off-grid
Switching



Insulation
testing




Black
start



Anti-islanding protection,
short-circuit protection,
Under/over-voltage
protection, overcurrent
protection

| Technical parameters: | Scopio AS100/125k-01 | Scopio AS200/250k-01 | Scopio AS500k-01 |
|-------------------------------------|---|------------------------|-------------------------|
| Photovoltaic input | | | |
| Input voltage range | 0~900V | | |
| MPPT voltage range | 313~900V (50k module)/394~900V (63k module) | | |
| Maximum number of modules | 2 | 4 | 8 |
| Maximum PV power | 100kW/120kW | 200kW/240kW | 400kW/480kW |
| Maximum input power per module | 50kW/60kW | | |
| Maximum input current per module | 160A | | |
| Battery input | | | |
| Battery voltage range | 672~864V | | |
| Number of batteries | 1-4 | 1-4 | 1-4 |
| Maximum battery charging current | 200A | 200A*2 | 200A*4 |
| Maximum battery discharging current | 200A | 200A*2 | 200A*4 |
| AC Grid-Connected | | | |
| Maximum input capacity | 250kVA | 500kVA | 1000kVA |
| Rated power | 100kW/125kW | 200kW/250kW | 500kW |
| Rated voltage | 400V | | |
| Frequency | 50/60Hz | | |
| Voltage range | -15%~15% | | |
| Maximum current | 167A/200A | 334A/400A | 800A |
| Overload capacity | 1.1 times for a long duration | | |
| Power factor | 0.99 | | |
| Wiring method | 3W+N+PE | | |
| AC off-grid | | | |
| Rated output power | 100kW/125kW | 200kW/250kW | 500kW |
| Rated output current | 200A | 400A | 800A |
| Rated output voltage | 400V | | |
| Rated frequency | 50/60Hz | | |
| THDU | <3% (linear load) | | |
| Basic parameters | | | |
| Working temperature | -30°C~60°C (Derating from >45°C) | | |
| Dimension | 880*920*2100mm (W*D*H) | 880*920*2320mm (W*D*H) | 1600*920*2320mm (W*D*H) |
| Weight | ~880kg | ~980kg | ~1760kg |
| Protection level | IP54 | | |
| Altitude | 4000m (Derating from >2000m) | | |
| Communication method | Ethernet/4G/RS485/CAN | | |



Note: Technical specifications are for reference only. Actual data is subject to the shipped product.