

Specifications (M: monocrystal, P: polycrystal)

<b>Module</b>	FS-M-380W~320W						
<b>Pmax</b>	380W	370W	360W	350W	340W	330W	320W
<b>Size and number of cells</b>	156*156mm 72Pcs/6*12						
<b>Tolerance</b>	±3%						
<b>Vmp(V)</b>	41.688	41.472	40.968	40.680	39.096	39.024	38.763
<b>Imp(A)</b>	9.37	9.29	9.10	8.99	8.93	8.91	8.86
<b>Voc(V)</b>	49.10	48.89	48.38	48.10	46.01	45.94	45.79
<b>Isc(A)</b>	9.71	9.66	9.53	9.46	9.42	9.41	9.37

<b>Module</b>	FS-M-300W~260W		
<b>Pmax</b>	300W	280W	260W
<b>Size and number of cells</b>	156*156mm 72Pcs/6*12		
<b>Tolerance</b>	±3%		
<b>Vmp(V)</b>	38.16	37.44	36.648
<b>Imp(A)</b>	8.65	8.57	8.48
<b>Voc(V)</b>	46.87	46.66	46.15
<b>Isc(A)</b>	9.27	9.2	9.17

<b>Max.Syst.Oper. Voltage</b>	1000V
<b>Dioders</b>	3 by-pass / 6 by-pass
<b>Dimension</b>	1956*992*40mm
<b>Weight</b>	22.5kgs
<b>Operate Temp.</b>	-40 ~ +85°C
<b>Relative humidity</b>	0 to 100%
<b>Resistances</b>	227g steel ball falls down from 1m high and 60m/s wind speed
<b>Warranty</b>	Pm is not less than 90% in 10 years and 80% in 25 years
<b>STC</b>	Irradiance 1000W/m <sup>2</sup> , module temperature 25°C, AM=1.5

